you can **Canon**

Digital Still Compact Cameras







PowerShot and Digital IXUS cameras feature the very best in Canon technologies and precision optics, all working in concert to deliver stunning results, shot after shot.

THE POWER BEHIND EVERY SHOT





Canon's revolutionary image processors: DIGIC II and the next-generation DIGIC III, lie at the core of every PowerShot and Digital IXUS camera. The massive processing capacity of DIGIC III paves the

way for advanced features such as Face Detection Technology and Red-Eye Correction, while exceptional processing speed delivers outstanding responsiveness, fast and accurate auto focus and extended continuous shooting. Linking all key camera functions for maximum efficiency, all DIGIC processors achieve brilliant image detail, clarity and colour reproduction, while delivering long, high quality movies and more shots from a single charge.





Available on selected models only

INTELLIGENT SCENE ANALYSIS BASED isaps on photospace

Like a built-in photographer's assistant, iSAPS is determining the optimal settings for each image even before you take a shot. It analyses the scene using PhotoSpace - an in-camera library of photographic data about the way people take pictures. It then controls the exposure, focus and white balance to ensure you get the best from every shot.






Canon Original Image

Pin-sharp clarity or the smallest detail

CAPTURE THE MEMORY

Canon Digital Still Cameras take photos that match the scene as you remember it. Simply being accurate is not enough. Pictures need to capture everything from ambience to stark reality. Rendering an image is a combination of exposure, colour balance and subject recognition.

Canon digital cameras render images that match the feelings you experienced when you pressed the shutter button. Exposure is accurate whatever the lighting conditions, even with off-centre subjects and low light. Colours appear as you remember them - blue skies stay blue, green leaves are green and skin tones remain beautifully natural.



Colour Reproduction based on memory colours

MAKE MORE OF THE MEGAPIXELS

Canon PowerShot and Digital IXUS cameras are equipped with a range of CCD sensor sizes: from 5.0 Megapixels for detailed, photolab quality prints up to A4 size - all the way to 10.0 Megapixels - for poster prints up to A2.



ISO ISO NR EXTENDED ISO SHOOTING

ISO 1600*, Canon Digital Still Cameras allow shooting in extremely low light conditions without a flash; great for maintaining a scene's ambience, such as in a restaurant or museum. For clean results at high ISO settings, Noise Reduction Technology harnesses the power of DIGIC III to suppress grain and speckle. The Digital IXUS 900 Ti and PowerShot G7 even have a dedicated super high-speed special scene mode that increases sensitivity to ISO 3200** for near-dark conditions where use of flash may be undesirable.

Advanced Lens Technology

With over 60 years of optical engineering experience, Canon continues to develop technologies that challenge the theoretical limits of lens performance.

Canon's aim has always been to produce lenses that perfectly capture life's most precious moments. Since the 1940s, Canon has made countless technical breakthroughs, including the world's first fluorite lens elements and zooms with optical Image Stabilisation.

An obsession for innovation has seen Canon register more zoom lens design patents in Japan than any other company.


Unlike some other manufacturers that use off-the-shelf components, Canon originates and produces its lenses using only Canon materials, know-how and machines. So only Canon makes Canon lenses.

HIGH PERFORMANCE LENSES

Every Canon Digital Still Camera features a high-performance lens. Using advanced glass moulding materials and techniques, the lenses are ultra-compact and deliver pin-sharp clarity. Images faithfully record the smallest details even in the most intricate pictures.

ULTRA-THIN PERFORMANCE LENSES

VALens Selected Digital IXUS cameras incorporate Canon's unique UA (Ultra-high refractive index Aspherical) lens technology to maintain seductively slender profiles without compromising on image quality and performance.



The Digital IXUS 850 IS features a compact 3.8x wide-angle (28mm equivalent) optical zoom lens that consists of 7 elements in 5 groups (including 1 double-sided UA lens)

OPTICAL STEADY SHOOTING

STABILIZER Camera shake whilst hand holding a camera can cause blurred photos. Canon's optical Image Stabiliser (IS) technology detects and corrects slight camera shake and ensures crisp, clear, shake-free images. IS is extremely helpful at slower shutter speeds, in low light situations and at full zoom.




Without IS





FAST AND QUIET ZOOMING

ULTRASONIC An Ultrasonic Motor on the PowerShot S3 IS ensures super-fast, near-silent zooming for stills or movie clips1 This highly efficient motor powers the zoom lens in and out smoothly, quietly and swiftly, so photographers can compose pictures at the spur of a moment. Its hushed zoom action is also great for movies, since it won't be heard on the sound track.

How the optical Image Stabiliser works.








PowerShot G7 PowerShot S3 IS PowerShot A710 IS PowerShot A570 IS DIGITAL IXUS 850 IS DIGITAL IXUS 800 IS

Creativity you control

Canon Digital Still Cameras are loaded with user-friendly functions that will help you get the best from Canon's inner technology and get consistently great results.





FACE DETECTION AF/AE/FE*

Utilising the power of DIGIC III, Canon's Face Detection Technology ensures superb people shots by automatically detecting subjects in the frame and setting the correct focus, flash level and exposure for up to nine faces.

ARTIFICIAL INTELLIGENCE AUTO FOCUS Automatically detects the closest object from nine fixed focusing areas and gives the optimum focus and exposure, even when your subject is off-centre.



FLEXIZONE AF/AE CONTROL*

FlexiZone AF/AE control lets you choose where to focus almost anywhere in the frame by moving manually the auto-focus window in the viewfinder. Perfect focus is then assured.

* Featured on selected models only, please see specifications for details



COLOURS THAT CAPTIVATE

Add a personal touch to your image or movie with **My Colors** Canon's My Colors¹. Choose from vivid blue for the sky, antique sepia for the portrait or classic black and white for the landscape. These creative options and many more - normally available only on a computer - can be applied directly from your camera, before or after the shot1

My Colors settings vary on selected models. Please refer to the technical specifications for details







SHOOTING MODES1:

A MODE FOR EVERY MOMENT

Canon Digital Still Cameras feature a huge range of preset automatic and creative shooting modes to help you get the most from every shot.

- AUTO
- PORTRAIT
- **LANDSCAPE**
- **⋈** NIGHT SNAPSHOT
- **SPORTS**
- AV APERTURE PRIORITY
- TV SHUTTER SPEED PRIORITY
- **C** CUSTOM
- **P** PROGRAM
- M MANUAL
- MOVIE
- STITCH ASSIST

SCN SPECIAL SCENE

This mode has automatically stored presets for shooting various scenes. You can select them to ensure the most appropriate settings, without having to use the manual controls.

- BEACH
- **M** INDOOR
- FIREWORKS

UNDERWATER

- **FOLIAGE**
- **8** SNOW
- KIDS & PETS
- ☑ NIGHT SCENE
- **AQUARIUM**
- S COLOR SWAP
- **A COLOR ACCENT**
- 3200 ISO 3200²
- Recording pixels fixed at 1600 x 1200.

Sharing made easy

Great photos deserve to be shared. Canon Digital Still Cameras and supplied software make it easier than ever to set your images free.



COMPREHENSIVE SOFTWARE

With Canon's outstanding supplied image management software you can edit and organise photos and movies or create albums of favourite images. ZoomBrowser EX (for Windows) and ImageBrowser (for Macintosh) allow you to transfer, browse, archive and retouch your photos with ease. Make dynamic slideshows or print photos in a variety of sizes, all with easy step-by-step selections. Add an extra dimension with sound effects, music or commentary. You can also resize images for sending via e-mail. With Photostitch, up to 26 separate images can be joined to create a single, seamless wide-format picture.



MACOE Open up a world of online digital photography with CANON iMAGE GATEWAY¹. Register your new Canon digital product today and GATEWAY start enjoying 100MB of online space for sharing photos with friends and family. Create themed photo albums with customised layouts and backgrounds. Order photo prints directly from your online photo album. Get hints, tips and ideas, plus customise your camera with great start-up images and sounds. With CANON iMAGE GATEWAY, you can. www.cig.canon-europe.com




PictBridge DIRECT PRINTING



With PictBridge support and the Print/Share button found on all current Canon Digital Still Cameras, getting quality photo prints of your favourite shots is as simple as 1. Connect, 2. Select, and 3. Print. Connect to any Canon SELPHY Compact Photo Printer or PIXMA printer, select the desired image, push 'Print/Share' and within seconds you'll be passing around a lab-quality photo print.





PowerShot

The power of PowerShot

Creative control - as much or as little as you like. Whether you're new to digital photography or looking to explore your creative side, PowerShot lets you move at your own speed.



From manual to fully automatic - and everywhere in between - you have the flexibility to take charge when you want to and let the camera take over when you don't.

Each model in the PowerShot range is packed with features and functions to make it versatile and easy to use. Preset automatic shooting modes - like Fireworks, Snow and Night Snapshot are quick to select, leaving you free to focus on capturing the moment. A wide range of optional accessories lets you stretch your creative limits when you're ready.

Putting you in control. That's the power of PowerShot.

Take control

At the top of the range sits Canon's flagship digital compact: the 10 Megapixel PowerShot G7.

Representing the pinnacle of compact digital photography, the PowerShot G7's classic design incorporates the very latest in photographic technologies, such as advanced DIGIC III image processing and a powerful 6x zoom lens with optical Image Stabilisation.

Canon's Speedlite flash range, and accessories such as a waterproof case to extend your shooting flexibility.

Offering complete creative control, the PowerShot G7 incorporates custom functions and many other analogue-style features normally found only on professional SLR cameras

It also has access to an advanced armoury of optional lenses,



PowerShot G7



lens accessories.













PowerShot S3 IS







The 7.1 Megapixel PowerShot A710 IS body so you can get closer to the action. results in low light, while showing off

PowerShot A710 IS

2.5" LCD screen.

- Optical Image Stabiliser for steady shots in low light and at full zoom
- Fast, superb results with DIGIC II, iSAPS,
- Full manual control
- Large LCD with wide viewing angle plus
- ISO 800 and High ISO Auto for flash-free
- 1cm Macro mode for close-up focusing
- Smooth 30 fps VGA and 60 fps QVGA
- · Widescreen (16:9) still image
- · Optional accessories include wide/tele/







Get down to business with the 10 Megapixel

PowerShot G7. With a 6x optical image

stabilised zoom, DIGIC III processor and

superb low light ISO 1600 performance,

accesses an extensive range of flash and

• Optical Image Stabiliser for steady shots

• DIGIC III processor and iSAPS for lightning

fast response, superb image quality and

• Face Detection AF/AE for precisely focused

• Classic design incorporating a large LCD

with wide viewing angle and anti-glare

Multi-control dial and dedicated ISO dial

• Full manual control with x2 custom

mode for extra low light and night

• Built-in (3-stop) Neutral Density filter

• My Colors for in-camera photo effects

 Accessory system includes wide/tele lenses, waterproof case and Canon

Speedlite flash range** * Recording pixels fixed at 1600 x1200

plus focus and auto exposure bracketing

settings and ISO 3200* special scene

in low light and at full zoom

advanced noise reduction

and exposed people shots

coating

with ISO 1600

photography

• 9-point AiAF and FlexiZone AF/AE

this supremely featured compact also









Featuring a 12x optical zoom with

Image Stabiliser, the PowerShot S3 IS

to super telephoto. Advanced video

this all-star performer.

and UD lens element

and FlexiZone AF/AE

results without flash

focusing

recording mode

and lens hood

* Depending on memory card used

setting and Sports mode

covers it all - from sweeping panoramas

functions, extensive shooting modes and

• Optical Image Stabiliser, fast USM zoom

• Extra long* VGA movies with Photo in

• Fast, superb results with DIGIC II, iSAPS

• Full manual control plus x1 custom

• My Colors for in-camera photo effects

• ISO 800 for great indoor and low light

• 0cm Super Macro mode for close-up

• Optional converter lenses, slave flash

• Impressive 2.0" vari-angle LCD

• Widescreen (16:9) still image

Movie feature and stereo sound

low light shooting capability complete









packs a powerful 6x zoom into its compact Optical Image Stabilisation ensures steady winning images is a joy on the large

- 9-point AiAF and FlexiZone AF/AE
- My Colors for in-camera photo effects
- optical viewfinder
- indoor and low light shooting
- Extra telephoto reach with Digital Tele-Converter & Safety Zoom
- movies with sound
- recording mode
- close-up lenses and waterproof case
- Conveniently powered by AA batteries

































PowerShot A640 PowerShot A630



waterproof case.

custom setting

• Full manual control plus x1

indoor and low light shooting

Tele-Converter & Safety Zoom

• Widescreen (16:9) still image

lenses and waterproof case

recording mode

PowerShot A630

• Extra telephoto reach with Digital

• My Colors for in-camera photo effects

• ISO 800 and High ISO Auto for flash-free

• 1cm Macro mode for close-up focusing

• Smooth 30 fps VGA movies with sound

• Optional accessories include wide/tele

Conveniently powered by AA batteries











photographers, pushing the boundaries See the world differently with the with optional lens accessories and full PowerShot A640 and PowerShot A630. manual exposure control. A 4x optical zoom with Image Stabilisation and DIGIC III Swivel the vari-angle screen and hold it high or low to explore new perspectives. with Face Detection Technology help you Expand your creative vision with a 4x optical find the perfect shot. zoom lens, optional lens accessories and

- superb image quality and advanced • Large vari-angle LCD enables creative noise reduction
- framing • Face Detection Technology with • Fast, superb results with DIGIC II, iSAPS, Red-Eye Correction in playback for 9-point AiAF and FlexiZone AF/AE great people shots
 - High ISO 1600 for flash-free indoor and low light shooting
 - Wide range of shooting modes include full manual control

• DIGIC III for lightning fast response,

- Smooth 30 fps VGA and 60 fps OVGA movies with sound
- LCD with Night Display and optical viewfinder
- Complete range of optional accessories includes wide/tele/close-up lenses, slave flash and waterproof case
- PictBridge and dedicated Print/Share button for one-touch printing and uploading
- Conveniently powered by AA batteries



PowerShot A570 IS

















PowerShot A560

- Easy to use with popular Scene Modes on the Mode Dial and one-touch record/review button
- · DIGIC III for lightning fast response, superb image quality and advanced noise reduction
- 9-Point AiAF and Face Detection AF/AE/FE for great people shots
- Red-Eye Correction in playback, using Face Detection Technology
- ISO 1600 and High ISO Auto for low light shooting
- LCD screen with Night Display and Grid Line Overlay
- My Colors* photo effects
- Smooth 30 fps VGA and 60 fps QVGA movies with sound
- PictBridge and dedicated Print/Share button for one-touch printing and uploading
- Conveniently powered by AA batteries

* See specifications for details



PowerShot A550





camera for your money.

record/review button

and 9-point AiAF

Grid Line Overlay



The PowerShot A550 features ISO 800

indoors and in other low light situations.

With 7.1 Megapixels and a 4x optical zoom,

so you can enjoy flash-free shooting

this compact performer offers a lot of

• Easy to use with popular Scene Modes

• Fast, sharp results with DIGIC II, iSAPS

• LCD with Night Display and selectable

• 13 versatile shooting modes plus

• Smooth 30 fps VGA and 60 fps

indoor and low light shooting

Print/Share button for one-touch

• Conveniently powered by AA batteries

QVGA movies with sound

• PictBridge and dedicated

printing and uploading

* See specifications for details

My Colors* in-camera photo effects

• ISO 800 and High ISO Auto for flash-free

on the Mode dial and one-touch









- Fast, superb results with DIGIC II, iSAPS
- 12 shooting modes include 8 easy-to-use
- My Colors** in-camera photo effects
- Record VGA movie clips with sound
- LCD with selectable Grid Line Overlay
- for sharp close-ups
- 3 attractive colour options*
- Easy direct printing and uploading with Print/Share button and PictBridge compatibility



PowerShot A460













- and 5-point AiAF
- Special Scene modes
- for in-camera, PC or TV playback
- for easy composition
- 1cm Super Macro mode
- Conveniently powered by AA batteries

* Some colour variations may not be available in some regions
** See specifications for details


























































Esther Berndsen Office manager "No postcard or souvenir I could buy would ever match





For more than a decade. IXUS has been changing our perception of what a camera should be. Today, the iconic IXUS has come to symbolize Canon design excellence, pure and simple.

Classic styling and cutting-edge performance have made the IXUS range of compact digital cameras one of the most successful ever. Canon first hit upon this winning combination in 1996. In the decade that has followed, IXUS has constantly re-invented itself, but always stayed true to its original vision: achieving the ideal balance of form and function. Whichever model you choose, the IXUS label ensures you'll find high-performance lenses, Canon's Visionary Technologies and an ultra-compact design that is often copied, but never equalled.

Enduring elegance

Strong yet lightweight with a beautiful silky touch, titanium is the perfect choice of metal for the outer case of Canon's irresistible Digital IXUS 900 Ti.

The camera's tactile perpetual curve design hints at the abundance of technologies poised just below the surface. To get the most from its 10 Megapixel resolution sensor, the Digital IXUS 900 Ti is powered by Canon's latest DIGIC III processor. DIGIC III provides the platform for advanced features such as Face Detection Technology and Noise Reduction

Technology, and handles complex rendering at high velocity - for responsive, fast, superb results that match the camera's beautiful looks.



DIGITAL IXUS 900 Ti





Undeniably exclusive, the titanium

combination of pioneering technology

and arresting design. Lead the pack with

Digital IXUS 900 Ti is the perfect

10 Megapixel resolution, DIGIC III

array of advanced features.

advanced noise reduction

super-processing and an irresistible

• Titanium construction with perpetual

curve design and touch control dial

• Face Detection AF/AE for precisely

focused and exposed people shots

• Super high-resolution LCD with

wide viewing angle

and High ISO Auto setting

• High-resolution XGA (15 fps) and

VGA (30 fps) movies with sound

• Extra telephoto reach with Digital

Tele-Converter & Safety Zoom

• My Colors for in-camera photo effects

• My Category function for faster image

searching, erasing, protecting, printing

and slideshows, all by image category

• Optional waterproof and soft leather cases

• DIGIC III processor and iSAPS for lightning

fast response, superb image quality and

• ISO 1600 for flash-free, low light shooting













DIGITAL IXUS 850 IS









Side-arm to the serious photographer, the 7.1 Megapixel Digital IXUS 850 IS is a milestone of technical excellence and discerning style. A 3.8x wide-angle lens takes in more of the scene - ideal for large group shots and breathtaking landscapes.

- Wide-angle (28mm) 3.8x zoom lens with optical Image Stabiliser
- Compact and stylish curvature design
- DIGIC III processor and iSAPS for lightning fast response, superb image quality and advanced noise reduction
- Face Detection AF/AE for precisely focused and exposed people shots
- Large LCD with wide viewing angle
- My Colors for in-camera photo effects
- Smooth 30 fps VGA movies with sound
- ISO 1600 for flash-free, low light shooting and High ISO Auto setting
- Extra telephoto reach with Safety Zoom
- My Category function for faster image searching, erasing, protecting, printing and slideshows, all by image category
- Optional waterproof and soft leather cases

The delightfully compact Digital IXUS 800 IS combines exquisite IXUS style with advanced features to satisfy the most demanding of photographers. A 4x optical zoom lens with optical Image Stabiliser and ISO 800 enable sharper flash-free shooting indoors.

- Delightfully compact with avant-garde two-tone finish
- Optical Image Stabiliser (IS) for steady shots in low light and at full zoom
- ISO 800 and optical IS reduce effects of camera shake and subject blur, enabling flash-free indoor shooting
- Fast, superb results with DIGIC II, iSAPS and 9-point AiAF
- Extra large 2.5" LCD with wide viewing angle
- My Colors for in-camera photo effects
- Long* 30 fps VGA and 60 fps QVGA movie clips with sound
- Widescreen (16:9) still image recording
- Easy direct printing and uploading with PictBridge and Print/Share button
- Optional waterproof and soft leather cases
- * Depending on memory card speed and capacity.

































DIGITAL IXUS 75







From its bold 'black circle' design motif to

innovative, touch-sensitive controls, the

An extra large 3.0" LCD, Canon's DIGIC III

processor and a host of advanced features

• Cutting edge design incorporating accents

• DIGIC III and iSAPS for fast response times,

ensure equally stunning performance.

of black and Touch Control Dial

Compact 3x optical zoom UA lens

superb image quality and advanced

• Face Detection AF/AE/FE and Red-Eye

• High resolution PureColor LCD with

for parties, restaurants and other

• Long* 30fps VGA movies including

button for quick image review

* Depending on memory card speed and capacity

Shortcut button and dedicated Playback

• High ISO 1600 and Auto ISO Shift - ideal

noise reduction

Correction in playback

wide viewing angle

low light environments

My Colors photo effects

Time Lapse Movie

Digital IXUS 75 is styled to stand out.







DIGITAL IXUS 70





Inspired by the timeless appeal of the very first IXUS, the Digital IXUS 70 is a masterpiece of minimalist design. Equipped with precision optics and leading technologies, this seductively slim camera offers exceptional performance to match its breathtaking looks.

- Sharp, minimalist design with slender all-metal body
- Compact 3x optical zoom UA lens
- DIGIC III and iSAPS for fast response times, superb image quality and advanced noise reduction
- Face Detection AF/AE/FE and Red-Eye Correction in playback
- High resolution PureColor LCD with wide viewing angle
- High ISO 1600 and Auto ISO Shift ideal for parties, restaurants and other low light environments
- My Colors photo effects
- Long* 30fps VGA movies including Time Lapse Movie
- Shortcut button for instant access to favorite functions

* Depending on memory card speed and capacity



DIGITAL IXUS 60











The exquisitely compact Digital IXUS 60 continues the IXUS tradition of graceful style with compelling design. A large screen and slender all-metal body conceal high performance optics and cutting edge Canon technology – for images that look as sharp as the camera that takes them.

- Elegant design with slender all-metal body
- Large LCD with wide viewing angle
- Fast, superb results with DIGIC II, iSAPS and 9-point AiAF
- My Colors for in-camera photo effects
- Long* 30 fps VGA and 60 fps QVGA movie clips with sound
- ISO 800 for flash-free indoor and low light shooting
- Widescreen (16:9) still image recording
- Easy direct printing and uploading with PictBridge and Print/Share button
- Optional waterproof and soft leather cases

* Depending on memory card speed and capacity



The result of decades of research, every Canon digital camera incorporates a wealth of features. To make it easy to distinguish between models, a summary of key features is listed in the chart below.

Feature Compatibility Chart

	POWERSHOT	PowerShot G7	PowerShot S3 IS	PowerShot A710 IS	PowerShot A640	PowerShot A630	PowerShot A570 IS	PowerShot A560	PowerShot A550	PowerShot A460	DIGITAL IXUS	Digital IXUS 900 Ti	Digital IXUS 850 IS	Digital IXUS 800 IS	Digital IXUS 75	Digital IXUS 70	Digital IXUS 60
Megapixels		10.0	6.0	7.1	10.0	8.0	7.1	7.1	7.1	5.0		10.0		6.0	7.1	7.1	6.0
Optical Zoom		6x	12x	бх	4x	4x	4x	4x	4x	4x		3x	3.8x	4x	3x	3x	3)
Optical Image Stabiliser (IS)		•	•	•	171	- 174	•	174	- 1/1	1/1		- JA	•	•	- J.	- JA	- 5,
DIGIC III		•					•	•				•	•		•	•	
DIGIC II			•	•	•	•			•	•				•			•
USM			•	_		-			_								
Red-Eye Correction							•	•							•	•	-
LCD Monitor		2.5"	2.0"	2.5"	2.5"	2.5"	2.5"	2.5"	2.0"	2.0"		2.5"	2.5"	2.5"	3.0"	2.5"	2.5
Vari-angle LCD Monitor			•		•	•									0.0		
Shooting Modes		25	20	20	21	21	19	14	13	12		18	17	16	17	17	16
FlexiZone AF/AE		•	•	•	•	•											
9-point AiAF		•		•	•	•	•	•	•			•	•	•	•	•	•
Face Detection Technology		•					•	•				•	•		•	•	
ISO 800		•	•	•	•	•	•	•	•			•	•	•	•	•	•
ISO 1600		•					•	•				•	•		•	•	
ISO 3200 (Special Scene Mode) ¹		•										•					
Digital Tele-Converter		•		•	•	•	•	•	•			•			•	•	
Safety Zoom		•		•	•	•	•	•	•	•		•	•		•	•	
My Colors		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
VGA (30 fps) movies		•	•	•	•	•	•	•	•			•	•	•	•	•	•
XGA (15 fps) movies		•										•					
Widescreen (16:9) still image recording		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
PictBridge		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
Direct Print		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
Print/Share button		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
USB 2.0 Hi-Speed		•	•	•	•	•	•	•	•			•	•	•	•	•	•
CANON IMAGE GATEWAY		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
Optional Tele/Wide Converter lens		•	•	•	•	•	•										
Optional Waterproof case		•		•	•	•	•					•	•	•	•	•	•

Recording pixels fixed at 1600 x 1200.



























SELPHY COMPACT PHOTO PRINTER

My world, My prints, My way

What if the moments of your life could be printed in full photo-lab quality at any moment of the day? SELPHY Compact Photo Printers produce vibrant colours and crisp details straight from your camera.




BRIGIT BOTTSE, NETHERLANDS

"Kids grow up so fast. I see changes from one day to the next. Digital photos are a great, inexpensive way to capture every precious moment. And thanks to SELPHY, I can print shots the instant after I take them. My parents especially love it. Every time they come to visit, they go home with photos already in hand!"

SELPHY ES1

For the ultimate ease, the SELPHY ES1 stands apart as the king of convenience.

Both ink and media are combined into a single integrated Easy Photo Pack, so it could not be easier to replace paper or swap between media types. And a 50 sheet capacity means you'll spend more time having fun printing than changing cartridges. A big, bright print-preview LCD makes it easy to review your photos and experiment with the host of creative printing possibilities, such as red-eye correction, image trim and colour effects. You can also use the dedicated creative photo printing button to produce fun layouts, suchs as calendars and photo albums, without the need for a computer. Incorporating a carry handle and retractable USB cable, the stylish vertical orientation design takes up a minimum of valuable shelving or desk space, keeping your home uncluttered. And with a DIGIC II processor, you can be assured of outstanding image quality every time.





SELPHY ES1

With one-touch operation, combined ink and media and an impressive 50-sheet capacity, the stylish SELPHY ES1 makes photo printing a pleasure. Add a 2.5" LCD screen, extensive creative options and outstanding print quality for the ultimate in compact photo printing.

- Integrated ink and media in one convenient Easy Photo Pack
- Compact, vertical design with carry handle and retractable USB cable
- Superior quality prints with DIGIC II
- User-friendly 2.5" colour LCD view, edit and print from Direct Print/PictBridge compatible cameras and most memory cards*
- Wireless printing from mobile phones with IrDA or optional Bluetooth adapter
- Optional battery pack for easy printing on
- Dedicated creative photo printing button for fun print layouts, including calendars
- Image enhancement including red-eye correction, image trim, and My Colors
- Long lasting 100-year* prints with instant dry, durable coating
- Economical home photo printing

* See specifications for details



SELPHY CP730

Easy to use and remarkably compact, the stylish SELPHY CP730 lets you create stunning photos of those special occasions direct from your digital camera. Enjoy onthe-spot printing wherever you are with the optional battery pack.

- Ultra compact photo printer with optional battery pack for printing on the move
- Prints direct from any PictBridge/Direct Print compatible camera or camcorder
- · Easy direct printing from most memory cards*
- High quality 100-year* prints with instant dry, durable coating
- User-friendly 2.0" colour LCD
- Quick start up and fast 58-second prints*
- Image trim and My Colors functionality for artistic prints
- Print from mobile phones with IrDA or optional Bluetooth adaptor
- Stylish design with retractable USB cable
- Range of print sizes with convenient ink/paper packs*
- * See specifications for details



SELPHY CP720

Now everyone can enjoy the fun of creating great photo prints at home. Affordable and easy to use, the ultra compact SELPHY CP720 is the perfect partner for your family's digital camera. Instant results at the touch of a button - direct from your camera or memory card.

- · Affordable home photo printing
- Easy enough for the whole family to enjoy
- Prints direct from any PictBridge/Direct Print compatible camera or camcorder
- · High quality 100-year* prints with instant dry, durable coating
- User-friendly 1.5" colour LCD view, edit and print direct from most memory cards*
- Quick start up and fast 58-second prints*
- Print from mobile phones with optional Bluetooth adapter
- Compact design with retractable USB cable
- Range of print sizes with convenient ink/paper packs
- * See specifications for details





































Print perfect photos in seconds CONNECT your camera or insert the the photo you want your pictures in memory card directly into - crop or trim on the a variety of sizes. your printer. camera or printer LCD. SELPHY To make direct printing even easier, all current Canon Digital Still Cameras have a Print/Share button that illuminates when ready and automatically prints the selected image when pressed.



The choice is yours

Not everyone wants a standard size print. Thankfully the SELPHY Compact Photo Printers are extremely accommodating. Choose from bordered and borderless postcard size, 100 x 200mm wide size¹, credit card size prints, stickers and even mini-stickers¹. Canon Digital Still Cameras give you the option to rotate the image 90 degrees or crop/zoom in on details – and with the latest Canon models you can also create ID Photo Prints and Movie Prints².


- SELPHY CP730 and SELPHY CP720 only.
- Options depend on camera, printer, printer tray and printing standard chosen.
 Only available on the SELPHY ES1

SELPHY Print Media and Accessories


Print Media for SELPHY ES1




Print Media for SELPHY CP730 and SELPHY CP720



Accessories







Conversion Lenses

A great benefit of digital photography is that the camera's LCD monitor shows exactly what the camera 'sees'. This opens the way for the use of conversion lenses, because you can see how additional lenses will affect the shot. Each lens in this exciting range is built with the exacting precision found in every Canon lens, to deliver superb quality as well as versatility.

WIDE ANGLE CONVERTER LENSES

Wide angle conversion lenses expand your frame so you get more in the shot – perfect for group shots and landscapes. They also help create unconventional perspectives on every-day subjects, giving photographs a strong sense of separation between subject and background.







Get a better sense of space with wide angle lenses

TELE CONVERTER LENSES

Tele converters bring distant subjects right up close, making them perfect for wildlife and sports photography.

Use a tele converter lens to take portraits from a discreet distance and capture natural, un-self-conscious expressions.







Close in on the action with a tele converter lens

CLOSE-UP CONVERTER LENSES

Close-up converters allow you to fill your frame with tiny objects, and to emphasise your subject with the shallow depth of field inherent with their use. Get right in close and capture the beauty of nature's miniature world: the patterned wing of a butterfly, the morning dew collected on spider's web, a flower petal's brilliant burst of colour.







Fill the frame with subject detail for greater impact with a close-up lens

Digital Still Compact Cameras



PowerShot S3 IS with lens adapter LA-DC58E (part of lens adapter and lens hood kit LAH-DC20) and wide angle converter WC-DC58A.

Flash Accessories

While the built-in flash on your Digital IXUS, A or S series PowerShot camera covers most day-to-day photography, some situations call for more flexibility. Seriously powered and firing in sync with your camera's built in flash without being connected, the High Power Flash HF-DC1 adds metres to your night range and opens the way for creative bounce flash, side and back fills. And with the hot shoe mount of the PowerShot G7, you can explore Canon's full Speedlite Flash accessory range for virtually unlimited creative lighting possibilities.

Power Supply

Next time you are documenting that once-in-a-lifetime occasion, be reassured with the knowledge that a fully charged back-up battery is at hand. Free from the worry of running out of power, you will take more photos, shoot more video and take greater enjoyment from reviewing and sharing your images. Canon batteries have a number of built-in features to ensure the safe and long use of your camera. Try adding an extra battery charger, AC adapter kit and car battery charger to your kit for the ultimate in digital flexibility.

Water-resistant Housings

Canon's inspired range of underwater and all-weather cases are sure to quicken the pulse of photographers with a passion for the outdoors. From surfing to diving, skiing to snorkelling; Canon gives you the freedom to fully explore your outdoor passions.



Waterproof Case (40m) For PowerShot A710 IS.


With protection to a depth of up to 40 metres, Canon's waterproof cases are an exciting addition to any scuba diver or snorkeller's kit. Cases include anti-fog, double-glass lens windows1 and a flash diffusion plate¹ to reduce the 'snow' effect caused by reflections off underwater particles. Big, robust coloured buttons allow easy operation even when wearing gloves.



WW-DC1 Waterproof Case Weight

COMPENSATION WEIGHTS

All divers know the importance of buoyancy compensation - the ability to adjust your weight underwater so that you neither rise to the surface nor sink to the bottom. A specially balanced and secure compensating weight system has been specifically designed to reduce the combined buoyancy of camera and case, so you and your camera are always operating at the same level.



Digital Still Compact Cameras

Accessories Compatibility Chart

						·s			· .										
					S	0	9	2	5	.00	.00	.00	S	5	8	8			
			POWERSHOT	5	PowerShot 53 IS	PowerShot A710 IS	PowerShot A640	PowerShot A630	PowerShot A5 70 IS	PowerShot A560	PowerShot A550	PowerShot A460	DIGITAL IXUS	Digital IXUS 900Ti	Digital IXUS 850 IS	Digital IXUS 80015	Digital IXUS 75	Digital IXUS 70	Digital IXUS 60
			S	ţ	t	ğ	ğ	ğ	ğ	ğ	ğ	ğ		Š	Š	Š	Š	Š	Š
			l ii	PowerShot G7	erS	erSt	erS	erS	erSt	erSt	erS	erS	ΤĀ	- E	- E		- E	<u>=</u>	- E
			8	Š	8	Š	8	8	8	8	8	8	<u> </u>	igi	igi	igi	igi	iĝi	igit
			_	_	_			_	_	_	_	_		_	_	_		_	
SOFT CASES																			
DCC-600				•															
DCC-400												•							
DCC-300							•	•											
DCC-90					•														
DCC-80									•	•	•								
DCC-70														•	•	•			
DCC-60																	•	•	•
SC-DC50				•															
WATER-RESISTANT HOUSINGS																			
WATERPROOF	Max.	Recommended																	
CASES	depth	amount of compensation																	
		weights (WW-DC11)																	
WP-DC4	40m	_																	•
WP-DC5	40m	-														•			-
WP-DC6	40m	3				•										-			
WP-DC7	40m	1				_								•					
WP-DC7	40m	2					•	•						_					
		_					•	•	-	-									
WP-DC9	40m			_											•				
WP-DC11	40m	3		•															
WP-DC12	40m	2							•										
WP-DC13	40m																_	•	
WP-DC14	40m																•		
CONVERSION LENSES ²				_		_		_	_										
Wide Converter				•	•	•	•	•	•	_									-
Tele Converter				•	•	•	•	•	•										
Close-up Lens					•	•			•										
FLASH																			
High-Power Flash HF-DC1				•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
Speedlite 580EX				•															
Speedlite 430EX				•															
Speedlite 220EX				•															
POWER SUPPLY																			
BATTERIES																			
NB-2LH				•															
NB-4L																	•	•	•
NB-5L														•	•	•			
NB4-300 ³					•	•	•	•	•	•	•	•							
BATTERY CHARGERS																			
CB-2LWE				•															
CB-2LVE																	•	•	•
CB-2LXE														•	•	•			
CBK4-300 ⁴					•	•	•	•	•	•	•	•							
CAR BATTERY CHARGERS																			
CBC-NB2				•															
AC ADAPTER KITS																			
CA-PS700					•														
ACK-600							•	•											
ACK-800						•			•	•	•	•							
ACK-DC10																	•	•	•
ACK-DC20				•															
ACK-DC30														•	•	•			
MISCELLANEOUS																			
CABLES																			
A/V Cable AVC-DC300				•		•	•	•	•	•	•	•		•	•	•	•	•	•
Stereo Video Cable STV-250N					•														
USB Interface Cable IFC-400PCU				•	•	•	•	•	•	•	•	•		•	•	•	•	•	•
STRAPS																			
Digital IXUS Metal Strap														•	•	•	•	•	•
Digital IXUS Leather Strap														•	•	•	•	•	•
																		$\overline{}$	

<sup>WW-DC1. Set of four weights including screws and pins
See chart below for lens and adapter specific information
A4A-size rechargeable baterries (charger not included)
Charger incl. 4AA-size rechargeable batteries</sup>

Conversion Lenses Compatibility Chart

	Standard Zoom Range ¹	Lens Adapter	Wi	de Converter	Tele C	Converter	Close-up Lens
	20011 Runge		Converter name	Specifications ¹	Converter name	Specifications ¹	
PowerShot G7	35 - 210mm	LA-DC58H	WC-DC58B	0.7x - max. 25mm	TC-DC58C	2x - max. 420mm	-
PowerShot 710 IS	35 - 210mm	LA-DC58G	WC-DC58N	0.7x - max. 25mm	TC-DC58N	1.75x - max. 368mm	250D (58mm)
PowerShot A640/A630	35 - 140mm	LA-DC58F	WC-DC58N	0.7x - max. 25mm	TC-DC58N	1.75x - max. 245mm	-
PowerShot S3 IS	36 - 432mm	LAH-DC20	WC-DC58A	0.75x - max. 27mm	TC-DC58B	1.5x - max. 648mm	500D (58mm)
PowerShot A570 IS	35 - 1/₁0mm	LA-DC52G	MC-DCE2	0.7v - may 25mm	TC-DCE2A	1.75v - may 37/5mm	250D (52mm)

Approx. 35mm equivalent

DIGITAL CAMERA		PowerShot G7	PowerShot S3 IS
IMAGE SENSOR	Type Effective Pixels	1/1.8" CCD Approx. 10.0M	1/2.5" CCD Addrox. 6.0M
IMAGE PROCESSOR	Type	DIGIC III with iSAPS technology	DIGIC II with iSAPS technology
LENS	Focal Length	7.4 - 44.4mm	6.0 - 72.0mm
		(35mm equivalent: 35 - 210mm)	(35mm equivalent: 36 - 432mm)
	Zoom	Optical 6x. Digital approx. 4x (with Digital Tele-Converter	Optical 12x. Digital approx. 4x ² . Combined approx. 48x
		approx. 1.4x or 2.3x and Safety Zoom 1)2. Combined approx. 24x	
		f/2.8-f/4.8	tion time
	Maximum f/number Construction	9 elements in 7 groups (1 double-sided aspherical element)	f/2.7 - f/3.5 11 elements in 9 groups (1 aspherical element, 1 UD element)
	Construction	9 elements in 7 groups (1 double-sided aspirental element)	11 elements in 9 groups (1 asphenical element, 1 ob element)
	Image Stabilisation	YES (shift-type)	YES (shift-type)
	Ultrasonic Motor (USM)	=	YES, zoom
FOCUSING	Туре	ΠL	TTL
	AF System/Points	AiAF (Face Detection / 9-point), 1-point AF	1-point AF (Any position is available)
	AF Last /AF Assist Dagge	(Any position is available or fixed centre)	On JOff Calcatable / VEF
	AF Lock/AF Assist Beam Closest Focusing Distance	On/Off Selectable / YES 1cm	On/Off Selectable / YES Ocm
EXPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot (centre or linked to Face Detection AF	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame)
EXTOSORE CONTROL	receining Flores	or FlexiZone AF frame)	Evaluative, centare weighted are tage, spot (centar or minera to locasting manne)
	AE Lock	YES	YES
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / 1/3 - 2 EV in 1/3 stop increments	+/- 2 EV in 1/3 stop increments / 1/3 - 2 EV in 1/3 stop increments
		HITTO HIS LIFER LAND CONTROL OF THE PARTY OF	NETO US LUCO L. CO. 402
SHUTTER	ISO Sensitivity ³	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600	AUTO, High ISO Auto, 80, 100, 200, 400, 800
SHUILEK	Speed	15 – 1/2,500 sec. (Available shutter speeds vary depending on the shooting mode)	15 – 1/3,200 sec. (Available shutter speeds vary depending on the shooting mode)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash,	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom
re onemice	Jennings	Underwater, Custom	2.2., 2.3) gray closed j, realigned, redolescene, redolescenen, reasil, custoff
VIEWFINDER	Viewfinder/Dioptre Correction	Real-image zoom, optical viewfinder / YES	EVF (0.33" type), approx. 115,000 pixels / YES
	•		7 7 7 7
LCD MONITOR	Monitor/Coverage	2.5" P-Si TFT, approx. 207,000 pixels / 100%	Vari-angle 2.0" Low temperature P-Si TFT, approx. 115,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation	3 levels with internal flash (13 levels with external EX Speedlites (4)). Safety FE	+/- 2 EV in 1/3 stop increments
	Flash Exposure Lock	YES	YES
	Built-in Flash Range	30cm - 4.0m (W) / 2.5m (T) (at ISO AUTO equivalent)	50cm - 5.2m (W) / 90cm - 4.0m (T) (at ISO AUTO equivalent)
	External Flash	E-TTL with EX series Speedlites 4, Canon's High Power Flash HF-DC1	Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom,
		(2 modes), Stitch Assist, Movie, Special Scene (Portrait, Landscape, Night Scene,	Portrait, Landscape, Night Scene, Sports, Stitch Assist, Movie, Special Scene
		Sports, Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks,	(Foliage, Snow, Beach, Fireworks, Indoor, Night Snapshot, Color Accent,
		Aquarium, Underwater, ISO 3200 ⁵ , Color Accent, Color Swap)	Color Swap).
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker
	riioto Lifects	Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)	Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
	Drive Modes	Single, Continuous, Self-Timer	Single, Continuous, Self-Timer
	Continuous Shooting	Continuous Shooting (Normal) approx. 2.0 fps 6, Continuous Shooting (AF)	High Speed at approx. 2.3 fps 6 (until memory card becomes full) ⁷
		approx. 0.8 fps ⁶ (until memory card becomes full) ⁷	Normal at approx. 1.5 fps 6 (until memory card becomes full) 7
DECORDING DIVELS /		(L) 3648 x 2736, (M1) 2816 x 2112, (M2) 2272 x 1704, (M3) 1600 x 1200,	(1) 204 (244 2. (144) 2272 4701 (142) 4 (200 4200 (5) (10 100
RECORDING PIXELS / COMPRESSION	Image Size	(S) 640 x 480, (W) 3648 x 2048	(L) 2816 x 2112, (M1) 2272 x 1704, (M2) 1600 x 1200, (S) 640 x 480, (W) 2816 x 1584
CONFRESSION	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L1)1024 x 768, 15 fps, (L2)640 x 480, 30/15 fps, (M)320 x 240, 30/15 fps,	(L)640 x 480, 30/15 fps (M)320 x 240, 60/30/15 fps
		(S)160 x 120, 15 fps	
	Movie Length	Up to 4GB or 1 hour (L1, L2 and M) 7	Up to 1GB or 1 hour ⁷
		Up to 3 mins (S) 7	
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File
		system, Digital Print Order Format [DPOF] Version 1.1 compliant	system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	AVI [Motion JPEG compression + WAVE (stereo)]
	Sound Files	WAVE (monaural)	WAVE (stereo)
DIRECT PRINT	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridg
		(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only
071150 55471/555	PictBridge	YES	YES
OTHER FEATURES	Red-Eye Correction	Start un impaga and campre serve de ensternication (Chart un image and camera counte sustantiantiant
	My Camera/My Category	Start-up image and camera sounds customisation / Image tagging feature	Start-up image and camera sounds customisation /—
	Sound Memo	Up to 60 sec. per image	Up to 60 sec. per image
	Intelligent Orientation Sensor	YES YES	YES
	Histogram	YES, live histogram	YES, live histogram
	Playback Zoom	Approx. 2x - 10x	2x-10x
	Self Timer	Approx. 2 or 10 sec. or Custom	Approx. 2 or 10 sec. or Custom
INTERFACE	Menu Languages	25 languages	23 languages
INTERFACE	Computer/Other	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)
MEMORY CARD	Туре	Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or	Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or
	.Jpc	MultiMediaCard (MMC), 32MB Memory Card supplied	MultiMediaCard (MMC), 16MB Memory Card supplied
			Caro Supplied
SUPPORTED OPERATING SYSTEM	PC	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2
	Macintosh	OS X v10.2 - 10.4	OS X v10.2 - 10.4
SOFTWARE	Browsing & Printing	ZoomBrowser EX / ImageBrowser	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch, Remote Capture	PhotoStitch, RemoteCapture
	Drivers	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)
DOWED SOURCE	Image Manipulation	Dachargapha Li ian Battar, ND 3111/ND 31	ArcSoft PhotoStudio
POWER SOURCE	Batteries	Rechargeable Li-ion Battery NB-2LH/NB-2L (NB-2LH battery and charger supplied)	4x Size-AA Alkaline or NiMH Batteries (NB4-300) (Alkalines supplied)
	A/C Power Supply	Optional, AC Adapter Kit ACK-DC20	Optional, Power Adapter CA-PS700
ACCESSORIES		See pages 60 - 65 for full accessories	See pages 60 - 65 for full accessories
PHYSICAL SPECIFICATIONS	Operating Environment	0 - 40°C, 10 - 90% humidity	0 - 40°C, 10 - 90% humidity
	Dimensions (W x H x D)	106.4 x 71.9 x 42.5mm (excluding protrusions)	113.4 x 78.0 x 75.5mm (excluding viewfinder-eyepiece & protrusions)
	Weight (body only)	Approx 320g	Approx 410a

See footnotes on page 162

Digital Still Compact Cameras

Digital Still Compact Cameras Specifications Chart

DIGITAL CAMERA	Ŧ	PowerShot A710 IS	PowerShot A640/PowerShot A630
MAGE SENSOR	Type Effective Pixels	1/2.5" CCD Approx. 7.1M	1/1.8" CCD Approx. 10.0M (PowerShot A640) / Approx. 8.0M (PowerShot A630)
MAGE PROCESSOR	Туре	DIGIC II with iSAPS technology	DIGIC II with iSAPS technology
ENS	Focal Length	5.8 - 34.8mm (35mm equivalent: 35 - 210mm)	7.3 - 29.2mm (35mm equivalent: 35 - 140mm)
	Zoom	Optical 6x. Digital approx. 4x (with Digital Tele-Converter approx. 1.5x or 1.9x and Safety Zoom 1) 2. Combined approx. 24x	Optical 4x. Digital approx. 4x (with Digital Tele-Converter approx. 1.4x or 2.3x (PowerShot A640), approx.1.6x or 2.0x (PowerShot A630) and Safety Zoom 1): Combined approx. 16x
	Maximum f/number Construction	f/2.8 - f/4.8 9 elements in 7 groups (1 aspherical element with both sides aspherical)	f/2.8 - f/4.1 8 elements in 7 groups (2 aspherical elements)
	Image Stabilisation	YES (shift-type)	-
FOCUSING	Type AF System/Points	9-point AIAF, 1-point AF (Any position is available or fixed centre)	TTL 9-point AiAF, 1-point AF (Any position is available or fixed centre)
	AF Lock/AF Assist Beam	On/Off Selectable / YES	On/Off Selectable / YES
	Closest Focusing Distance	1cm	1cm
EXPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame)	Evaluative, Centre-weighted average, Spot (centre or linked to focusing frame)
	AE Lock	Locked when shutter button is pressed half way	Locked when shutter button is pressed half way
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
CILLITTED	ISO Sensitivity ³	AUTO, High ISO Auto, 80, 100, 200, 400, 800	AUTO, High ISO Auto, 80, 100, 200, 400, 800
SHUTTER	Speed	15 – 1/2,000 sec. (Available shutter speeds vary depending on the shooting mode)	15 – 1/2,500 sec. (Available shutter speeds vary depending on the shooting mode)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H,	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Underwater, Custr
		Underwater, Custom	
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR	Monitor/Coverage	2.5" P-Si TFT, approx. 115,000 pixels / 100%	Vari-angle 2.5" P-Si TFT, approx. 115,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments	+/- 2 EV in 1/3 stop increments
	Flash Exposure Lock Built-in Flash Range	YES 55cm - 3.5m (W) / 2.5m (T) (at ISO AUTO equivalent)	YES 45cm - 4.2m (W) / 3m (T) (at ISO AUTO equivalent)
	External Flash	Canon's High Power Flash HF-DC1	Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Portrait,	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom, Por
		Landscape, Night Scene, Stitch Assist, Movie, Special Scene (Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Underwater, Color Accent, Color Swap)	Landscape, Night Scene, Stitch Assist, Movie, Special Scene (Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Underwater, Color Accent Color Swap)
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Lighter/Darker Skin Tone, Positive Film, Vivid Blue, Vivid Red, Vivid Green, Custom Color)	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Lighter/Darker Skin Tone, Positive Film, Custom Color)
	Drive Modes Continuous Shooting	Single, Continuous, Self-Timer Approx. 1.7 fps ⁶ (until memory card becomes full) ⁷	Single, Continuous, Self-Timer Approx.1.5 fps 6 (until memory card becomes full) 7 (PowerShot A640) / Approx.1.8 fps 6 (until memory card becomes full) 7 (PowerShot A630)
RECORDING PIXELS / COMPRESSION	Image Size	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200	(L) 3648 x 2736, (M1) 2816 x 2112, (M2) 2272 x 1704, (W) 3648 x 2048 (PowerShot A640) / (L) 3264 x 2448, (M1) 2592 x 1944, (M2) 2048 x 1536, (W) 3264 x 1832 (PowerShot A630) / (M3) 1600 x 1200, (S) 640 x 480, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L)640 x 480, (M)320 x 240, 30/15 fps (M)320 x 240, 60 fps (S)160 x 120, 15 fps	(L)640 x 480, 30/15 fps (M)320 x 240, 30/15 fps (S)160 x 120, 15 fps
	Movie Length	Up to 1GB or 1 hour (L and M, 30/15 fps)	Up to 1GB or 1 hour (L and M). Up to 3 min (S) ⁷
		Up to 1 min (M, 60 fps). Up to 3 min (S) 7	
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	AVI [Motion JPEG compression + WAVE (monaural)]
	Sound Files	WAVE (monaural)	WAVE (monaural)
DIRECT PRINT	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridg (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only
	PictBridge	YES	YES
OTHER FEATURES	Red-Eye Correction	=	-
	My Camera/My Category	Start-up image and camera sounds customisation /—	Start-up image and camera sounds customisation /—
	Sound Memo	Up to 60 sec. per image	Up to 60 sec. per image
	Intelligent Orientation Sensor	YES	YES
	Histogram	YES	YES
	Playback Zoom	Approx. 2x - 10x	Approx. 2x - 10x
	Self Timer	Approx. 2 or 10 sec. or Custom	Approx. 2 or 10 sec. or Custom
WITER CO.	Menu Languages	25 languages	25 languages
NTERFACE	Computer/Other	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)
MEMORY CARD	Туре	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 16MB Memory Card supplied	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memony Card supplied (Powershot A640) / 16f Memony Card supplied (PowerShot A630)
SUPPORTED OPERATING SYSTEM	PC	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2
	Macintosh	OS X v10.2 - 10.4	OS X v10.2 - 10.4
SOFTWARE	Browsing & Printing	ZoomBrowser EX / ImageBrowser	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch	PhotoStitch, RemoteCapture (PowerShot A640)
	Drivers	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)
POWER SOURCE	Image Manipulation Batteries	2x Size-AA Alkaline or NiMH Batteries (NB4-300) (Alkalines supplied)	- 4x Size-AA Alkaline or NiMH Batteries (NB4-200) (Alkalines supplied)
			·
ACCESSORIES	A/C Power Supply	Optional, AC Adapter Kit ACK-800	Optional, AC Adapter CA-PS500
PHYSICAL SPECIFICATIONS	Operating Environment	See pages 60 – 65 for full accessories 0 – 40°C, 10 – 90% humidity	See pages 60 − 65 for full accessories 0 − 40°C, 10 − 90% humidity
	Dimensions (W x H x D)	97.5 x 66.5 x 41.2mm (excluding protrusions)	109.4 x 66.0 x 49.1mm (excluding protrusions)
	Weight (body only)	Approx. 210g	Approx. 245g

DIGITAL CAMERA		PowerShot A570 IS	PowerShot A560
IMAGE SENSOR	Туре	1/2.5" CCD	1/2.5° CCD
IMAGE DDOGEGOD	Effective Pixels	Approx. 7.1M DIGIC III with iSAPS technology	Approx. 7.1M DIGIC III with iSAPS technology
IMAGE PROCESSOR LENS	Type Focal Length	5.8 - 23.2mm	5.8 - 23.2mm
22113	. oca. zenga.	(35mm equivalent: 35 - 140mm)	(35mm equivalent: 35 - 140mm)
	Zoom	Optical 4x. Digital approx 4x ² (with Digital Tele-Converter approx 1.5x or 1.9x and	Optical 4x. Digital approx 4x ² (with Digital Tele-Converter approx 1.5x or 1.9x
		Safety Zoom 1)2. Combined approx. 16x	and Safety Zoom 1)2. Combined approx 16x
	Maximum f/number	f/2.6-f/5.5	f/2.6-f/5.5
	Construction	7 elements in 5 groups (2 aspherical elements)	7 elements in 5 groups (2 aspherical elements)
			, , , , , , , , , , , , , , , , , , , ,
	Image Stabilisation	YES (shift-type)	-
FOCUSING	Type AF System/Points	TTL AiAF (Face Detection / 9-point), 1-point AF (fixed centre)	TTL AiAF (Face Detection / 9-point), 1-point AF (fixed centre)
	Ar System/Points	AIAF (Face Detection / 9-point), 1-point AF (fixed centre)	AIAF (race Detection / 9-point), 1-point AF (lixed certile)
	AF Lock/AF Assist Beam	On/Off Selectable / YES	On/Off Selectable / YES
	Closest Focusing Distance	5cm	5cm
EXPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot (centre or linked to	Evaluative, Centre-weighted average, Spot (centre or linked to
	API . d.	Face Detection AF frame)	Face Detection AF frame)
	AE Lock	Locked when shutter button is pressed half way	On/Off Selectable
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
	ISO Sensitivity 3	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600
SHUTTER	Speed	15 - 1/2,000 sec.	15 - 1/2,000 sec.
		(Available shutter speeds vary depending on the shooting mode)	(Available shutter speeds vary depending on the shooting mode)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H,	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
WHITE BALANCE	Settings	Underwater, Custom	nato, pagnyni, cioudy, rungsten, ruorestent, ruorestent A, Custom
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR	Monitor/Coverage	2.5" Amorphous silicon TFT, approx. 115,000 pixels / 100%	2.5" Amorphous silicon TFT, approx. 115,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation Flash Exposure Lock	+/- 2 EV in 1/3 stop increments, Face Detection FE	YES
	Built-in Flash Range	45cm - 3.5m (W) / 2.2m (T) (at ISO AUTO equivalent)	45cm – 3.5m (W) / 2.2m (T) (at ISO AUTO equivalent)
	External Flash	Canon's High Power Flash HF-DC1	Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Program AE, Shutter priority AE, Aperture priority AE, Manual, Portrait,	Auto, Manual, Portrait, Landscape, Night Snapshot, Indoor, Kids & Pets, Movie,
		Landscape, Night Snapshot, Kids & Pets, Indoor, Stitch Assist, Movie, Special	Special Scene (Foliage, Snow, Beach, Fireworks, Night Scene, Aquarium)
		Scene (Night Scene, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater)	
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Custom Color (limited))	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Custom Color (limited))
	PHOTO EHECTS	11y Colors (Off, Vivia, Neutral, Septa, Black & Willie, Custoffi Color (Illiffied))	rry Colors (Oil, Vivia, Nedural, Sepia, Black & Writte, Custoffi Color (Illifficed))
	Drive Modes	Single, Continuous, Self-Timer	Single, Self-Timer
	Continuous Shooting	Approx. 1.7 fps ⁶ (until memory card becomes full) ⁷	Approx. 1.7 fps ⁶ (until memory card becomes full) ⁷
RECORDING PIXELS /	Image Size	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200,	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200,
COMPRESSION	illage 3ize	(S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200	(S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L)640 x 480, (M)320 x 240, 30/15 fps, 320 x 240, 60 fps,	(L)640 x 480, 30/15 fps, (M)320 x 240, 60/30/15 fps, (S)160 x 120, 15 fps
	Marie Lawreth	(S)160 x 120, 15 fps	Hata ICD and houself and M 70 MC (an)
	Movie Length	Up to 4GB or 1 hour (L and M, 30/15 fps) Up to 1 min (M, 60 fps). Up to 3 min (S) 7	Up to 4GB or 1 hour (L and M, 30/15 fps) Up to 1 min (M, 60 fps). Up to 3 min (S) ⁷
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File
==		system, Digital Print Order Format [DPOF] Version 1.1 compliant	system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	AVI [Motion JPEG compression + WAVE (monaural)]
DIRECT PRINT	Sound Files Canon Printers	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge
DIRECT PRINT	Canon runcers	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)
		, and a second of the princip only)	Complete Com
	PictBridge	YES	YES
OTHER FEATURES	Red-Eye Correction	YES, in playback	YES, in playback
	My Camera/My Category Sound Memo	I In to 60 sec per image	Up to 60 sec. per image
	Intelligent Orientation Sensor	Up to 60 sec. per image YES	YES YES
	Histogram	YES	YES
	Playback Zoom	Approx. 2x - 10x	Approx. 2x - 10x
	Self Timer	Approx. 2 or 10 sec. or Custom	Approx. 2 or 10 sec. or Custom
INTEDEACE	Menu Languages	25 languages	25 languages
INTERFACE	Computer/Other	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)
MEMORY CARD	Туре	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or
-	•1	MultiMediaCard (MMC), 16MB Memory Card supplied	MultiMediaCard (MMC), 16MB Memory Card supplied
SUPPORTED OPERATING SYSTEM	PC	Windows® 2000 SP4 / XP / XP SP1-2 / Vista	Windows® 2000 SP4 / XP / XP SP1-2 / Vista
SOFTWARE	Macintosh Browsing & Printing	OS X v10.3 - 10.4 ZoomBrowser EX / ImageBrowser	OS X v10.3 – 10.4 ZoomBrowser EX / ImageBrowser
SOLIMANE	Other	PhotoStitch	PhotoStitch
	Drivers	TWAIN (2000)	TWAIN (2000)
	Image Manipulation	-	=
POWER SOURCE	Batteries	2x Size-AA Alkaline or NiMH Batteries (NB4-300) (Alkalines supplied)	2x Size-AA Alkaline or NiMH Batteries (NB4-300) (Alkalines supplied)
	A/C Dower Supply	Optional AC Adaptor Vit ACV 900	Ontional AC Adaptor Vit ACV 900
ACCESSORIES	A/C Power Supply	Optional, AC Adapter Kit ACK-800 See pages 60 - 65 for full accessories	Optional, AC Adapter Kit ACK-800 See pages 60 – 65 for full accessories
PHYSICAL SPECIFICATIONS	Operating Environment	0 - 40°C, 10 - 90% humidity	0 - 40°C, 10 - 90% humidity
22	Dimensions (W x H x D)	89.5 x 64.3 x 42.8mm	91.2 x 64.0 x 43.1mm
	Weight (body only)	175g	165g
ee footnotes on page 162			

See footnotes on page 162

Digital Still Compact Cameras

Digital Still Compact Cameras Specifications Chart

DIGITAL CAMERA		PowerShot A550	PowerShot A460
IMAGE SENSOR	Туре	1/2.5" CCD	1/3" CCD
	Effective Pixels	Approx. 7.1M	Approx. 5.0M
IMAGE PROCESSOR	Туре	DIGIC II with iSAPS technology	DIGIC II with iSAPS technology
LENS	Focal Length	5.8-23.2mm	5.4 - 21.6mm
	7	(35mm equivalent: 35 - 140mm)	(35mm equivalent: 38 - 152mm)
	Zoom	Optical 4x. Digital approx 4x ² (with Digital Tele-Converter approx 1.5x or 1.9x and Safety Zoom ¹) ² . Combined approx 16x	Optical 4x. Digital approx. 4x (with Safety Zoom 1) (still images), 2x (movies). Combined approx. 16x (still images), 8.1x (movies) 2
	Maximum f/number	f/2.6 - f/5.5	f/2.8 - f/5.8
	Construction	7 elements in 5 groups (2 aspherical elements)	7 elements in 6 groups (1 aspherical element)
	Image Stabilisation	-	-
FOCUSING	Type	TL	TL
	AF System/Points	9-point AiAF, 1-point AF (fixed centre)	5-point AiAF, 1-point AF (fixed centre)
	AF Lock/AF Assist Beam	On/Off Selectable / YES	Locked when shutter button is pressed half way / YES
	Closest Focusing Distance	5cm	1cm
EXPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot (centre)	Evaluative, Centre-weighted average, Spot (centre)
			2.2.2.2.2) centre magnico arstage, sport(centre)
	AE Lock	On/Off Selectable	Locked when shutter button is pressed half way
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
	ISO Sensitivity ³	AUTO, High ISO Auto, 80, 100, 200, 400, 800	AUTO, 80, 100, 200, 400
SHUTTER	Speed	15 - 1/2,000 sec.	15 - 1/2,000 sec.
		(Available shutter speeds vary depending on the shooting mode)	(Available shutter speeds vary depending on the shooting mode)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR	Monitor/Coverage	2.0" P-Si TFT, approx. 86,000 pixels / 100%	2.0" P-Si TFT, approx. 86,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation	- Lies	-
	Flash Exposure Lock	YES	- 17 7.0 (NO / 2.0 /T) (-NCO NETO
	Built-in Flash Range External Flash	45cm – 3.5m (W) / 2.2m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1	47cm - 3.0m (W) / 2.0m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Manual, Portrait, Landscape, Night Snapshot, Indoor, Kids & Pets, Movie,	Auto, Manual, Super Macro, Movie, Special Scene (Portrait, Night Snapshot, Kids &
SHOUTING	rioucs	Special Scene (Foliage, Snow, Beach, Fireworks, Night Scene)	Pets, Indoor, Foliage, Snow, Beach, Fireworks)
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Custom Color (limited))	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Custom Color (limited))
	Drive Modes	Single, Self-Timer	Single, Self-Timer
	Continuous Shooting	Approx. 1.4 fps 6 (until memory card becomes full) 7	Approx. 1.5 fps 6 (until the memory card is full) 7
RECORDING PIXELS / COMPRESSION	Image Size	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200	(L) 2592 x 1944, (M1) 2048 x 1536, (M2) 1600 x 1200, (S) 640 x 480, (W) 2592 x 1456, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L)640 x 480, 30/15 fps, (M)320 x 240, 60/30/15 fps, (S)160 x 120, 15 fps	(L)640 x 480, 10 fps (M)320 x 240, 30 fps, (S)160 x 120, 15 fps
			(7)
	Movie Length	Up to 1GB or 1 hour (L and M, 30/15 fps)	Up to 1GB or 1 hour (L and M)
		Up to 1 min (M, 60 fps). Up to 3 min (S) 7	Up to 3 min (S) ⁷
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Marias	AVI (Motion IDEC compression - MAVE (managed)	AVI [Motion IDEC compression]
	Movies Sound Files	AVI [Motion JPEG compression + WAVE (monaural)] WAVE (monaural)	AVI [Motion JPEG compression] WAVE (monaural)
DIRECT PRINT	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge
DIRECT PRINT	Canon Printers	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)
	PictBridge	YES	YES
OTHER FEATURES	Red-Eye Correction	-	-
	My Camera/My Category	- Illan CO	— Mrs
	Sound Memo	Up to 60 sec. per image	YES
	Intelligent Orientation Sensor Histogram	YES YES	_
	Playback Zoom	Approx. 2x - 10x	Approx. 2x - 10x
	Self Timer	Approx. 2 or 10 sec. or Custom	Approx. 2 or 10 sec. or Custom
	Menu Languages	25 languages	25 languages
INTERFACE	Computer/Other	USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC)	USB (Mini-B, MTP, PTP) / A/V output (PAL/NTSC)
MEMORY CARR	-	Server Dishel (CD) Code of the Code (CD) Code of the Code (CD) Cod	Complicit (CD) Control of the District Control of the Control of t
MEMORY CARD	Туре	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 16MB Memory Card supplied	Secure Digital (SD) Card or Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 16MB Memory Card supplied
SUPPORTED OPERATING SYSTEM	PC	Windows® 2000 SP4 / XP / XP SP1-2 / Vista	Windows® 2000 SP4 / XP / XP SP1-2 / Vista
SOLI ONIED OF ENATING STREET	Macintosh	0S X v10.3 - 10.4	OS X v10.3 = 10.4
SOFTWARE	Browsing & Printing	ZoomBrowser EX / ImageBrowser	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch	PhotoStitch
	Drivers	TWAIN (2000)	TWAIN (2000)
	Image Manipulation	=	-
POWER SOURCE	Batteries	2x Size-AA Alkaline or NiMH Batteries (NB4-300) (Alkalines supplied)	2x Size-AA Alkaline or NiMH Batteries (Alkalines supplied)
ACCECCODIEC	A/C Power Supply	Optional, AC Adapter Kit ACK-800	Optional, AC Adapter Kit ACK-800
ACCESSORIES	Operating Environment	See pages 60 – 65 for full accessories	See pages 60 – 65 for full accessories
PHYSICAL SPECIFICATIONS	Operating Environment	0 - 40°C, 10 - 90% humidity	0 - 40°C, 10 - 90% humidity
	Dimensions (W x H x D) Weight (body only)	91.2 x 64.0 x 43.1mm 160g	106 x 51.8 x 40.2mm Approx. 165g
	rreight (body only)	Tody	прргод. 1009

Digital Juli Compa		6	
DIGITAL CAMERA		Digital IXUS 900 Ti	Digital IXUS 850 IS
IMAGE SENSOR	Туре	1/1.8" CCD	1/2.5* CCD
INVESTIGATION OF THE PROPERTY	Effective Pixels	Approx. 10.0M	Approx. 7.1M
IMAGE PROCESSOR LENS	Type Focal Length	DIGIC III with iSAPS technology 7.7 - 23.1mm	DIGIC III with iSAPS technology 4.6 - 17.3mm
LLNJ	rocai Lengui	(35mm equivalent: 37 - 111mm)	(35mm equivalent: 28 - 105mm)
	Zoom	Optical 3x. Digital approx. 4x (with Digital Tele-Converter approx. 1.4x or 2.3x and Safety Zoom 1) 2. Combined approx. 12x	Optical 3.8x. Digital approx. 4x (with Safety Zoom 1) 2. Combined approx. 15x
	Maximum f/number Construction	f/2.8 - f/4.9 7 elements in 5 groups (2 aspherical elements)	f/2.8 - f/5.8 7 elements in 5 groups (1 double-sided aspherical element)
	Image Stabilisation	-	YES (shift-type)
FOCUSING	Type AF System/Points	TTL AiAF (Face Detection / 9-point), 1-point AF (fixed centre)	TTL AiAF (Face Detection / 9-point), 1-point AF (fixed centre)
	AF Lock/AF Assist Beam	On/Off Selectable / YES	On/Off Selectable / YES
	Closest Focusing Distance	5cm	3cm
EXPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot	Evaluative, Centre-weighted average, Spot
		(centre or linked to Face Detection AF frame)	(centre or linked to Face Detection AF frame)
	AE Lock	On/Off Selectable	On/Off Selectable
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
S.W.TTER	ISO Sensitivity ³	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600
SHUTTER	Speed	15 – 1/2,000 sec. (Shutter speeds of 1 sec. and more available in Long Shutter Mode only)	15 – 1/1,600 sec. (Shutter speeds of 1 sec. and more available in Long Shutter Mode only)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR	Monitor/Coverage	2.5" P-Si TFT, approx. 230,000 pixels / 100%	2.5" P-Si TFT, approx. 207,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation	- VFC	- VEC
	Flash Exposure Lock Built-in Flash Range	YES 70cm F 1m (NA) / 7 1m (T) (at ISO ALITO occident)	YES FOCOM (A Down (AA) / 2 Down (T) (at ISO ALITO equipolant)
	External Flash	30cm - 5.1m (W) / 3.1m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1	50cm - 4.0m (W) / 2.0m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Manual, Digital Macro, Color Accent, Color Swap, Stitch Assist, Movie,	Auto, Manual, Digital Macro, Color Accent, Color Swap, Stitch Assist, Movie,
5.00.110	rioues	Special Scene (Portrait, Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater, ISO 32003)	Special Scene (Portrait, Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater)
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
	Drive Modes Continuous Shooting	Single, Continuous, Self-Timer Approx. 2.1 fps ⁶ (until memory card becomes full) ⁷	Single, Continuous, Self-Timer Approx. 1.7 fps 6 (until memory card becomes full) ⁷
RECORDING PIXELS / COMPRESSION	Image Size	(L) 3648 x 2736, (M1) 2816 x 2112, (M2) 2272 x 1704, (M3) 1600 x 1200, (S) 640 x 480, (W) 3648 x 2048, (Postcard Date Imprint) 1600 x 1200	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L1)1024 x 768, 15 fps, (L2)640 x 480, 30/15 fps, (M)320 x 240, 30/15 fps,	(L)640 x 480, 30/15 fps (M)320 x 240, 60/30/15 fps (S)160 x 120, 15 fps
	Piovics	(S)160 x 120, 15 fps	(E)040 x 400, 307 13 lp3 (11)320 x 240, 007307 13 lp3 (3)100 x 120, 13 lp3
	Movie Length	Up to 4GB or 1 hour (L2 and M) 7. Up to 3 mins (L1 and S) 7	Up to 4GB or 1 hour (L and M, 30/15 fps) 7 Up to 3 mins (S) 7
	. rone zangar	op to 100 of 1 hour (to take 1), 1 op to 3 hims (to take 3)	Up to 1 min (M, 60 fps) 7
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	AVI [Motion JPEG compression + WAVE (monaural)]
	Sound Files	WAVE (monaural)	WAVE (monaural)
DIRECT PRINT	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)
	PictBridge	YES	YES
OTHER FEATURES	Red-Eye Correction	-	-
	My Camera/My Category	Start-up image and camera sounds customisation /	Start-up image and camera sounds customisation /
	C	Image tagging feature	Image tagging feature
	Sound Memo	Up to 60 sec per image	Up to 60 sec per image
	Intelligent Orientation Sensor Histogram	YES YES	YES YES
	Playback Zoom	Approx. 2x - 10x	Approx. 2x - 10x
	Self Timer	Арргох. 2 x = 10x Approx. 2 or 10 sec. or Custom	Approx. 2 or 10 sec. or Custom
	Menu Languages	25 languages	25 languages
INTERFACE	Computer/Other	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)	USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)
MEMORY CARD	Туре	Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied	Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 16MB Memory Card supplied
SUPPORTED OPERATING SYSTEM	PC	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2	Windows® 98SE / ME / 2000 SP4 / XP / XP SP1-2
	Macintosh	0SXv10.2 - 10.4	OS X v10.2 - 10.4
SOFTWARE	Browsing & Printing	ZoomBrowser EX / ImageBrowser	ZoomBrowser EX / ImageBrowser
	Other	PhotoStitch	PhotoStitch
	Drivers	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)	TWAIN (Windows® 98 / 2000), WIA (Windows® ME)
POWER SOURCE	Image Manipulation Batteries	Rechargeable Li-ion Battery NB-5L (battery and charger supplied)	Rechargeable Li-ion Battery NB-5L (battery and charger supplied)
	A/C Dower Cumby	Ontional AC Adapter kit ACK DC70	Optional AC Adaptor kit ACK DC70
ACCESSORIES	A/C Power Supply	Optional, AC Adapter kit ACK-DC30 See pages 60 - 65 for full accessories	Optional, AC Adapter kit ACK-DC30 See pages 60 – 65 for full accessories
PHYSICAL SPECIFICATIONS	Operating Environment	0 - 40°C, 10 - 90% humidity	0 - 40°C, 10 - 90% humidity
	Dimensions (W x H x D)	91.2 x 59.6 x 28.2mm (excluding protrusions)	89.5 x 58.0 x 25.1mm (excluding protrusions)
	Weight (body only)	Approx. 165g	Approx. 150g

See footnotes on page 162

Digital Still Compact Cameras

Digital Still Compact Cameras Specifications Chart

DIGITAL CAMERA		Digital IXUS 800 IS	Digital IXUS 75
IMAGE SENSOR	Туре	1/2.5" CCD	1/2.5" CCD
WACE BROCESCOR	Effective Pixels	Approx. 6.0M	Approx. 7.1M DIGIC III with iSAPS technology
MAGE PROCESSOR ENS	Type Focal Length	DIGIC II with iSAPS technology 5.8 - 23.2mm	5.8 - 17.4mm
ENS	rocal Length	(35mm equivalent: 35 - 140mm)	(35mm equivalent: 35 - 105mm)
	Zoom	Optical 4x. Digital approx. 4x (2). Combined approx. 16x	Optical 3x. Digital approx $4x^2$ (with Digital Tele-Converter approx 1.5x or 1.9x and Safety Zoom 1) 2. Combined approx 12x
	Maximum f/number Construction	f/2.8 - f/5.5 7 elements in 5 groups (2 aspherical elements, including 1 UA element)	f/2.8 - f/4.9 6 elements in 5 groups (2 UA elements)
	Image Stabilisation	YES (shift-type)	- elements in 5 gloups (2 OA elements)
OCUSING	Туре	TL (Similary)	π.
	AF System/Points	9-point AiAF, 1-point AF (fixed centre)	AiAF (Face Detection / 9-point), 1-point AF (fixed centre)
	AF Lock/AF Assist Beam Closest Focusing Distance	On/OffSelectable / YES 2cm	On/Off Selectable / YES 3cm
XPOSURE CONTROL	Metering Modes	Evaluative, Centre-weighted average, Spot (centre)	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre)
	AE Lock	On/Off Selectable	On/Off Selectable
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
SHUTTER	ISO Sensitivity ³ Speed	AUTO, High ISO Auto, 80, 100, 200, 400, 800 15 – 1/1,600 sec.	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600 15 – 1/1,500 sec.
HOTTER	speed	(Shutter speeds of 1 sec. and more available in Long Shutter Mode only)	(Shutter speeds of 1 sec. and more available in Long Shutter Mode only)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	-
.CD MONITOR	Monitor/Coverage	2.5" P-Si TFT, approx. 173,000 pixels / 100%	3.0" P-Si TFT, approx. 230,000 pixels / 100%
LASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation Flash Exposure Lock	YES	Face Detection FE YES
	Built-in Flash Range	50cm - 3.5m (W) / 2.0m (T) (at ISO AUTO equivalent)	50cm - 3.5m (W) / 2.0m (T) (at ISO AUTO equivalent)
	External Flash	Canon's High Power Flash HF-DC1	Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Manual, Digital Macro, Portrait, Night Snapshot, Stitch Assist, Movie, Special Scene (Foliage, Snow, Beach, Fireworks, Underwater, Indoor, Kids & Pets, Color Accent, Color Swap)	Auto, Manual, Digital Macro, Color Accent, Color Swap, Stitch Assist, Movie, Special Scene (Potrait, Night Snapshot, Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater)
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darks Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
	Drive Modes Continuous Shooting	Single, Continuous, Self-Timer Approx. 2.1 fps ⁶ (until memory card becomes full) ⁷	Single, Continuous, Self-Timer Approx. 1.7 fps ⁶ (until memory card becomes full) ⁷
RECORDING PIXELS / COMPRESSION	Image Size	(L) 2816 x 2112, (M1) 2272 x 1704, (M2) 1600 x 1200, (S) 640 x 480, (W) 2816 x 1584, (Postcard Date Imprint) 1600 x 1200	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L)640 x 480, 30/15 fps (M)320 x 240, 60/30/15 fps (S)160 x 120, 15 fps	(L)640 x 480, 30/15 fps, (M)320 x 240, 60/30/15 fps. (S)160 x 120, 15 fps (Time Lapse) 640 x 480, 0.5/1 fps (Playback 15 fps)
	Movie Length	Up to 1GB or 1 hour (L and M, 30/15 fps) ⁷ Up to 3 mins (S) ⁷ , Up to 1 min (M, 60 fps) ⁷	Up to 4GB or 1 hour (L and M, 30/15 fps) ⁷ , Up to 3 mins (S) ⁷ , Up to 1 min (M, 60 fps) ⁷ , Up to 120 mins (Time Lapse) ⁷
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format (DPOF) Version 1.1 compliant	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
			AVI [Motion JPEG compression + WAVE (monaural)]
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	
DIRECT PRINT	Movies Sound Files Canon Printers	AVI [Motion JPEG compression + WAVE (monaural)] WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge
DIRECT PRINT	Sound Files Canon Printers	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl
	Sound Files Canon Printers PictBridge	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES
	Sound Files Canon Printers	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation /
	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / —	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature
	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd, (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec, per image
	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES
	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES YES Approx. 2x - 10x	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x – 10x
	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom
OTHER FEATURES	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES 4pprox. 2 v - 10x Approx. 2 v - 10x Approx. 2 o 10 sec. or Custom 23 languages	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2 x - 10x Approx. 2 or 10 sec. or Custom 25 languages
OTHER FEATURES NTERFACE	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC)	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC)
DTHER FEATURES NTERFACE MEMORY CARD	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd, (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / AVV output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied
DTHER FEATURES NTERFACE MEMORY CARD	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista
OTHER FEATURES NTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memony Card supplied Windows* 985E / ME / 2000 SP4 / XP / XP SP1-2 0 SX V102 - 10.4	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridd (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES YES Approx. 2x - 10x Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows* 2000 SP4 / XP / XP SP1-2 / Vista OS XV10.3 - 10.4
OTHER FEATURES NTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows*9 85E / ME / 2000 SP4 / XP / XP SP1-2 0S X V10.2 - 10.4 ZoomBrowser EX / ImageBrowser	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PixtBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 Ianquages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS X V10.3 - 10.4 ZoomBrowser EX / ImageBrowser
OTHER FEATURES NTERFACE 1EMORY CARD SUPPORTED OPERATING SYSTEM	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows* 985E / ME / 2000 SP4 / XP / XP SP1-2 OS XY10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers on YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS XY1.0.3 – 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch
OTHER FEATURES NTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows* 985E / ME / 2000 SP4 / XP / XP SP1-2 OS X 10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (Windows* 98 / 2000), WIA (Windows* ME) Arcsoft PhotoStudio	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PixtBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers on YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES YES YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 Ianguages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS XV10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (2000)
OTHER FEATURES NTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation Batteries	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 OS X v10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (Windows® 98 / 2000), WIA (Windows® ME) ArcSoft PhotocStudio Rechargeable Li-ion Battery NB-SL (battery and charger supplied)	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES. YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2x - 10x Approx. 2x - 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows ⁶ 2000 SP4 / XP / XP SP1-2 / Vista 0S X V10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStich TWAIN (2000) — Rechargeable Li-ion Battery NB-4L (battery and charger supplied)
DIRECT PRINT OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE POWER SOURCE	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows* 985E / ME / 2000 SP4 / XP / XP SP1-2 OS X 10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (Windows* 98 / 2000), WIA (Windows* ME) Arcsoft PhotoStudio	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers onl YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 Ianguages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / AVV output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS XV10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoSitich TWAIN (2000)
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE POWER SOURCE	Sound Files Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation Batteries	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows* 985£ / ME / 2000 SP4 / XP / XP SP1-2 OS X v10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (Windows* 98 / 2000), WIA (Windows* ME) ArcSoft PhotoStudio Rechargeable Li-ion Battery NB-SL (battery and charger supplied) Optional, AC Adapter kit ACK-DC30	WAVE (monaural) Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBrid (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES YES Approx. 2x - 10x Approx. 2x

			11
DIGITAL CAMERA		Digital IXUS 70	Digital IXUS 60
IMAGE SENSOR	Туре	1/2.5" CCD	1/2.5" CCD
	Effective Pixels	Approx. 7.1M	Approx. 6.0M
IMAGE PROCESSOR	Туре	DIGIC III with iSAPS technology	DIGIC II with iSAPS technology
LENS	Focal Length	5.8 - 17.4mm	5.8 - 17.4mm
		(35mm equivalent: 35 - 105mm)	(35mm equivalent: 35 - 105mm)
	Zoom	Optical 3x Digital approx 4x ² (with Digital Tele-Converter approx 1.5x or 1.9x and Safety Zoom 1) ² . Combined approx 12x	Optical 3x. Digital approx. 4x ² . Combined approx. 12x
	Maximum f/number	f/2.8 - f/4.9	f/2.8-f/4.9
	Construction	6 elements in 5 groups (2 UA elements)	6 elements in 5 groups (2 UA elements)
	Image Stabilisation	-	-
FOCUSING	Туре	П	П
	AF System/Points	AiAF (Face Detection / 9-point), 1-point AF (fixed centre)	9-point AiAF, 1-point AF (fixed centre)
	AF Lock/AF Assist Beam	On/Off Selectable / YES	On/Off Selectable / YES
	Closest Focusing Distance	3cm	3cm
EXPOSURE CONTROL	Metering Modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average,	Evaluative, Centre-weighted average, Spot (centre)
		Spot (centre)	
	AE Lock	On/Off Selectable	On/Off Selectable
	Exposure Compensation/AEB	+/- 2 EV in 1/3 stop increments / —	+/- 2 EV in 1/3 stop increments / —
CHILITIED	ISO Sensitivity ³	AUTO, High ISO Auto, 80, 100, 200, 400, 800, 1600	AUTO, High ISO Auto, 80, 100, 200, 400, 800
SHUTTER	Speed	15 – 1/1,500 sec. (Shutter speeds of 1 sec. and more available in Long Shutter Mode only)	15 - 1/1,500 sec. (Shutter speeds of 1 sec. and more available in Long Shutter Mode only)
WHITE BALANCE	Settings	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom	Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER	Viewfinder	Real-image zoom, optical viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR	Monitor/Coverage	2.5" P-Si TFT, approx. 230,000 pixels / 100%	2.5" P-Si TFT, approx. 173,000 pixels / 100%
FLASH	Modes	Auto, Manual Flash On / Off	Auto, Manual Flash On / Off
	Flash Exposure Compensation	Face Detection FE	-
	Flash Exposure Lock	YES	YES
	Built-in Flash Range External Flash	50cm – 3.5m (W) / 2.0m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1	50cm = 3.5m (W) / 2.0m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1
SHOOTING	Modes	Auto, Manual, Digital Macro, Portrait, Night Snapshot, Color Accent, Color Swap,	Auto, Manual, Digital Macro, Portrait, Night Snapshot, Stitch Assist, Movie,
SHOOTING	modes	Auto, Mariual, Digital Macio, Portrait, Nigrit Shapshot, Color Accent, Color Swap, Stitch Assist, Movie, Special Scene (Kids & Pets, Indoor, Foliage, Snow, Beach, Fireworks, Aquarium, Underwater)	Scene (Foliage, Snow, Beach, Fireworks, Underwater, Indoor, Kids & Pets, Color Accent, Color Swap)
	Photo Effects	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)	My Colors (Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter/Darke Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
	Drive Modes Continuous Shooting	Single, Continuous, Self-Timer Approx. 1.7 fps 6 (until memory card becomes full) 7	Single, Continuous, Self-Timer Approx. 2.1 fps 6 (until memory card becomes full) 7
RECORDING PIXELS / COMPRESSION	Image Size	(L) 3072 x 2304, (M1) 2592 x 1944, (M2) 2048 x 1536, (M3) 1600 x 1200, (S) 640 x 480, (W) 3072 x 1728, (Postcard Date Imprint) 1600 x 1200	(L) 2816 x 2112, (M1) 2272 x 1704, (M2) 1600 x 1200, (S) 640 x 480, (W) 2816 x 1584, (Postcard Date Imprint) 1600 x 1200
	Compression	Superfine, Fine, Normal	Superfine, Fine, Normal
	Movies	(L)640 x 480, 30/15 fps, (M)320 x 240, 60/30/15 fps, (S)160 x 120, 15 fps (Time Lapse) 640 x 480, 0.5/1 fps (Playback 15 fps)	(L)640 x 480, 30/15 fps (M)320 x 240, 60/30/15 fps (S)160 x 120, 15 fps
	Movie Length	Up to 4GB or 1 hour (L and M, 30/15 fps) ⁷ , Up to 3 mins (S) ⁷ Up to 1 min (M, 60 fps) ⁷ , Up to 120 mins (Time Lapse) ⁷	Up to 1GB or 1 hour (L and M, 30/15 fps) ⁷ , Up to 3 mins (S) ⁷ Up to 1 min (M, 60 fps) ⁷
FILE TYPES	Still Image Type	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant	JPEG compression, (Exif 2.2 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format (DPOF) Version 1.1 compliant
	Movies	AVI [Motion JPEG compression + WAVE (monaural)]	AVI [Motion JPEG compression + WAVE (monaural)]
	Sound Files	WAVE (monaural)	WAVE (monaural)
DIDECT DRINT			
DIRECT PRINT	Canon Printers	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only)	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or
DIRECT PRINT	Canon Printers PictBridge	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES	Canon SELPHY Compact Photo Printers and PXMA Printers supporting PictBric (ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers on YES
DIRECT PRINT OTHER FEATURES	Canon Printers PictBridge Red-Eye Correction	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers on YES —
	Canon Printers PictBridge	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation /	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or
	Canon Printers PictBridge Red-Eye Correction My Camera/My Category	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / —
	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image
	PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES
	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES
	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2x – 10x	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x – 10x
	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom
OTHER FEATURES	PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 - 0 To sec. or Custom 25 languages	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages
OTHER FEATURES	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom
OTHER FEATURES	PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / AVV output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC),
OTHER FEATURES INTERFACE MEMORY CARD	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hii-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied
OTHER FEATURES	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 Ianguages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers on YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 – 10.4	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x – 10x Approx. 2x – 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 OS XV10.2 – 10.4
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows* 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 - 10.4 ZoomBrowser EX / ImageBrowser	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 05 X v 10.2 - 10.4 ZoomBrowser EX / ImageBrowser
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS XY10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers o YES
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows* 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 - 10.4 ZoomBrowser EX / ImageBrowser	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers o YES
OTHER FEATURES INTERFACE MEMORY CARD	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS XY10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Multi-MediaCard (MMC), 16 NB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 OS XY10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStich
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation Batteries	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (2000) — Rechargeable Li-ion Battery NB-4L (battery and charger supplied)	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE POWER SOURCE	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoSitich TWAIN (2000) Rechargeable Li-ion Battery NB-4L (battery and charger supplied) Optional, AC Adapter kit ACK-DC10	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 OS XV10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoSitich TWAIN (Windows® 98 / 2000), WIA (Windows® ME) ArcSoft PhotoStudio Rechargeable Li-ion Battery NB-4L (battery and charger supplied) Optional, AC Adapter kit ACK-DC10
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE POWER SOURCE ACCESSORIES	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation Batteries A/C Power Supply	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 2s languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS X10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoSitich TWAIN (2000) Rechargeable Li-ion Battery NB-4L (battery and charger supplied) Optional, AC Adapter kit ACK-DC10 See pages 60 - 65 for full accessories	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers or YES
OTHER FEATURES INTERFACE MEMORY CARD SUPPORTED OPERATING SYSTEM SOFTWARE POWER SOURCE	Canon Printers PictBridge Red-Eye Correction My Camera/My Category Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages Computer/Other Type PC Macintosh Browsing & Printing Other Drivers Image Manipulation Batteries	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers only) YES YES, in playback Start-up image and camera sounds customisation / Image tagging feature Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 25 languages USB 2.0 Hi-Speed (Mini-B, MTP, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, Secure Digital High-Capacity (SDHC) Card or MultiMediaCard (MMC), 32MB Memory Card supplied Windows® 2000 SP4 / XP / XP SP1-2 / Vista OS Xv10.3 - 10.4 ZoomBrowser EX / ImageBrowser PhotoSitich TWAIN (2000) Rechargeable Li-ion Battery NB-4L (battery and charger supplied) Optional, AC Adapter kit ACK-DC10	(ID Photo Print, Fixed Size Print and Movie Print on SELPHY CP & ES printers o YES — Start-up image and camera sounds customisation / — Up to 60 sec. per image YES Approx. 2x - 10x Approx. 2x - 10x Approx. 2 or 10 sec. or Custom 23 languages USB 2.0 Hi-Speed (Mini-B, PTP) / A/V output (PAL/NTSC) Secure Digital (SD) Card, MultiMediaCard (MMC), 16MB Memory Card supplied Windows® 985E / ME / 2000 SP4 / XP / XP SP1-2 OS XV10.2 - 10.4 ZoomBrowser EX / ImageBrowser PhotoStitch TWAIN (Windows® 98 / 2000), WIA (Windows® ME) ArcSoft PhotoStudio Rechargeable Li-ion Battery NB-4L (battery and charger supplied) Optional, AC Adapter kit ACK-DC10

See footnotes on page 162

Compact Photo Printers

SELPHY Printers Specifications Chart

RINTER		SELPHY ES1	SELPHY CP730
INTING SYSTEM	Method	Dye-sublimation thermal transfer printing system, with DIGIC II processor	Dye-sublimation thermal transfer printing system
	Maximum Resolution	300 x 600 dpi	300 x 300 dpi
	Colours	3 colour inks with over coating, B/W (Black ink with overcoating) up to 256 levels per colour (24 bit colour depth)	3 colour inks with over coating, 256 levels per colour (24 bit colour depth)
EDIA & CARTRIDGE	Postcard Size	148 x 100mm - [Easy Photo Pack E-P50,	148 x 100mm - [KP-36IP, KP-72IP, KP-108IP]
		Easy Photo Pack E-P100, Easy Photo Pack E-P25BW]	
	Wide Size L Size	440.000.00 [Free Physic Dods [Free	100 x 200mm - [KW-24IP] 1
	L Size	119 x 89mm = [Easy Photo Pack E-L50, Easy Photo Pack E-L100]	119 x 89mm - [KL-36IP] ¹
	Credit Card Size	86 x 54mm - [Easy Photo Pack E-C25]	86 x 54mm - [KC-36IP] ¹
	Credit Card Size Stickers	86 x 54mm - [Easy Photo Pack EC-25L]	86 x 54mm - [KC-18IF] ¹
	Mini Stickers	-	22.0 x 17.3mm (x8 stickers on one sheet) – [KC-18IL] ¹
	Ink Cartridge	Included with media	Included with media
	Image Longevity	(Ink / Paper Integrated Cartridge) 100 Years Print ⁶	100 Years Print ⁶
IEDIA INPUT	Sheet Feeder	Auto feed from integrated cartridge	Auto feed from paper cassette
RINT SPEEDS	Postcard Size	Approx. 69 sec. ⁴	Approx. 58 sec. ⁴
	Wide Size	<u> </u>	Approx. 73 sec. 4
	L Size Credit Card Size	Approx. 61 sec. 4 Approx. 53 sec. 4	Approx. 50 sec. 4 Approx. 31 sec. 4
	Credit Card Size Stickers	Approx. 53 sec. 4 Approx. 53 sec. 4	Approx. 31 sec. 4 Approx. 31 sec. 4
	Mini Stickers	=	Approx. 31 sec. 4
RINTING	Print Modes	All Image Print ² , Auto Compensation ² , Borderless, Bordered, Creative Print ² , Date Print ² , DPOF Image Print ² , File Name Print ² , Fixed Size Layout ² , ID Photo Print ² , Movie Print ² , My Colors (10 modes) ² , Red-eye correction ² , Single Image Print ² , Trimming Print ² , 2-up, 4-up and 8-up Layout ²	All Image Print ² , Borderless, Bordered, Date Print ² , DPOF Image Print ² , File Name Print ² , Fixed Size Layout ² , ID Photo Print ² , Image Optimisation ² , Movie Print ² , My Colors (4 modes) ² , Single Image Print ² , Trimming Print ² , 2-up, 4-up and 8-up Layout ²
PRINT METHOD	Direct Printing From a Camera	Canon Direct Print compliant, PictBridge compliant	Canon Direct Print compliant, PictBridge compliant
	Direct From a Memory Card	Supported card types: Compact Flash card, Memory stick, Memory Stick Pro, Memory Stick Pro Duo ⁵ , Memory Stick Duo ⁵ , Microdrive, miniSD card ⁵ , miniSDHC memory card ⁵ , Multimedia card, SD memory card, SDHC memory card, RS-MMC ⁵ , xD-Picture card ⁵	Supported card types: Compact Flash, Memory Stick, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick DUO, Microdrive, miniSD Card, miniS DHC memory card, Multimedia Card, SD memory card, SDHC Memory card, RS-MMC, xD-Picture Card ⁵
	Direct From a Camera Phone	Optional Bluetooth® Unit BU-20 (printing from some mobile camera phones & PDAs) 7, IrDA (printing from some mobile camera phones) 3	Optional Bluetooth® Unit BU-20 (printing from some mobile camera phones & PDAs) ⁷ , IrDA (printing from some mobile camera phones) ³
	Print From a Computer	YES, requires standard USB cable	YES, requires standard USB cable
NTERFACE	Camera	Integrated USB cable (Mini-B), USB type A port on printer, Wi-Fi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless Print Adapter WA-1E)	Integrated USB cable (Mini-B), USB type A port on printer, Wi-Fi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless Print Adapter WA-1E)
	Computer	USB type B port on printer	USB type B port on printer
	LCD Monitor	2.5° Colour LCD viewer with multi-language User Interface 8	2.0" Colour LCD with icon based Graphical User Interface
UPPORTED OPERATING SYSTEM	PC	Windows® 2000 SP4 / XP SP1-2	Windows® 2000 SP4 / XP SP1-2
	Macintosh	OS X v10.2 - v10.4	OS X v10.2 - v10.4
OFTWARE	Browsing & Printing	PC: ZoomBrowser EX, Easy-PhotoPrint Mac: ImageBrowser	PC: ZoomBrowser EX, Easy-PhotoPrint, PhotoStitch Mac: ImageBrowser, PhotoStitch
	Drivers	PC / Mac	PC / Mac
OWER SOURCE	A/C Power Supply	YES, supplied	YES, supplied
	Battery Pack	YES, optional (Approx 50 + Postcard Size / L size prints per full charge)	YES, optional (Approx. 36 + Postcard Size prints per full charge)
	Power Consumption	Approx. 4W (standby), approx. 70W (printing)	Approx. 4W (standby), approx. 60W (printing)
CCESSORIES	Case	-	CP Printer Carrying Case DCC-CP1
	Paper Cassette	Not required	Postcard Size paper cassette [PCP-CP100], Wide paper cassette [PCW-CP100], L size paper cassette [PCL-CP100], Card Size [PCC-CP100]
	Power Supply & Battery Chargers	Battery Pack NB-ES1L	Battery Pack NB-CP2L
		BU-20 Bluetooth® Unit for printing from	BU-20 Bluetooth® Unit for printing from
	Other	compatible camera phones and PDAs ⁷	compatible camera phones and PDAs 7
HYSICAL SPECIFICATIONS	Other Operating Environment	compatible camera phones and PDAs ⁷ 5° - 40°C, 20 - 80% humidity	
PHYSICAL SPECIFICATIONS		compatible camera phones and PDAs ⁷	compatible camera phones and PDAs ⁷

SELPHY Printers Specifications Chart

		3
PRINTER PRINTING SYSTEM	Method	SELPHY CP720 Dye-sublimation thermal transfer printing system
PRINTING STSTEM	riculou	bye-subilifiation thermal datisfer printing system
	Maximum Resolution	700 4 700 44
	Colours	300 x 300 dpi 3 colour inks with over coating,
		256 levels per colour (24 bit colour depth)
MEDIA & CARTRIDGE	Postcard Size	148 x 100mm - [KP-36IP, KP-72IP, KP-108IP]
	Wide Size	100 x 200mm - [KW-24IP] ¹
	L Size	119 x 89mm - [KL-36IP] ¹
	Credit Card Size	86 x 54mm - [KC-36IP] ¹
	Credit Card Size Stickers	86 x 54mm - [KC-18IF] ¹
	Mini Stickers	22.0 x 17.3mm
		(x8 stickers on one sheet) – [KC-18IL] ¹
	Ink Cartridge	Included with media
MEDIA INPUT	Image Longevity Sheet Feeder	100 Years Print ⁶ Auto feed from paper cassette
-		
PRINT SPEEDS	Postcard Size Wide Size	Approx. 58 sec. 4 Approx. 73 sec. 4
	L Size	Approx. 53 sec. 4
	Credit Card Size	Approx. 31 sec. 4
	Credit Card Size Stickers Mini Stickers	Approx. 31 sec. 4 Approx. 31 sec. 4
PRINTING	Print Modes	All Image Print ² , Borderless, Bordered, Date Print ² , DPOF Image Print ² ,
		File Name Print ² , Fixed Size Layout ² , ID Photo Print ² , Image Optimization ² ,
		Movie Print ² , Single Image Print ² , Trimming Print ² , 2-up, 4-up and 8-up Layout ²
PRINT METHOD	Direct Printing From a Camera	Canon Direct Print compliant, PictBridge compliant
		Pictoritye compilant
	Direct From a Memory Card	Supported card types: Compact Flash, Memory Stick, Memory Stick PRO,
		Memory Stick PRO Duo, Memory Stick DUO, Microdrive, miniSD Card, mini SDHC memory card, Multimedia Card, SD memory card,
		SDHC Memory card, RS-MMC, xD-Picture Card ⁵
	Direct From a Camera Phone	Optional Bluetooth® Unit BU-20
		(printing from some mobile camera phones & PDAs) ⁷
	Print From a Computer	YES, requires standard USB cable
INTERFACE	Camera	Integrated USB cable (Mini-B), USB type A port on printer,
		Wi-Fi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless Print Adapter WA-1E)
		Wileless Fillit Adapter WA-TE)
	Committee	LIFD to a D and to a sixter
	Computer LCD Monitor	USB type B port on printer 1.5" Colour LCD with icon based Graphical User Interface
		· ·
SUPPORTED OPERATING SYSTEM	PC	Windows® 2000 SP4 / XP SP1-2
	Macintosh	05Xv10.2 - v10.4
SOFTWARE	Browsing & Printing	PC: ZoomBrowser EX, Easy-PhotoPrint, PhotoStitch Mac: ImageBrowser, PhotoStitch
		riae. inagenowser, rinousulai
201122 501125	Drivers	PC / Mac
POWER SOURCE	A/C Power Supply Battery Pack	YES, supplied —
	,	
	Power Consumption	Approx. 4W (standby),
	Tower Consumption	approx. 60W (printing)
ACCESSORIES	Case	CP Printer Carrying Case DCC-CP1
	Paper Cassette	Postcard Size paper cassette [PCP-CP100],
		Wide paper cassette [PCW-CP100],
		L size paper cassette [PCL-CP100], Card Size [PCC-CP100]
	Power Supply & Battery Chargers	-
	Other	BU-20 Bluetooth® Unit for printing from
		compatible camera phones and PDAs ⁷
PHYSICAL SPECIFICATIONS	Operating Environment	5 – 40°C, 20 – 80% humidity
	Dimensions (W x H x D)	178.0 x 125.0 x 63.0mm
	Weight	930g (Excluding ink and paper cassettes)
		(cacading nix did paper cassenes)

Footnotes for SELPHY Printers Specifications Chart on pages 161 and 162

All data is based on Canon's standard testing methods. Subject to change without notice.

- 1 Requires optional paper cassette
- Modes/features available may differ dependent on camera model or use of memory card to print
- 3 Pictures must be taken in the JPEG format and transferred using the IrOBEX protocol
- Print speed can vary dependent on data size, memory card and capacity
- 5 Requires adapter (sold separately)
- 5 Requires adapter (sold separately)
 6 To test the image permanence of prints that are stored in an album, we use an accelerated testing method as how the image permanence of silver-halide photo papers are measured when stored in dark places. Print samples are printed with the optical density of 1.0 (each Bk, C, M, Y). The samples are kept in a certain environment of high temperature and 50% humidity.

 The rate of the decrease in the optical density and rate of yellow discoloration are recorded. The recorded results are then converted to the length of time when print image is kept in an environment of 23°C/50% humidity.

 «Trietain for estimation of print longevity» The point where monochromatic/reflective optical density shows loss of 30% (starting density of 1.0).

 7 Mobile phones and PDA's must be Bluetooth® enabled and support

- 7 Mobile phones and PDA's must be Bluetooth® enabled and support Bluetooth® version 1.1 or above Photo printing only pictures must be in the IPEG format. Bluetooth® operation depends on the device and software version used
- 8 21 languages supported are: English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Russian, Portuguese, Hungarian, Polish, Czech, Greek, Turkish, Simplified Chinese, Chinese, Korean, Japanese

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

- 1 Depending on the image size selected
- Digital zoom available for still image and standard movie modes only. Optical zoom may not be available during movie recording
- Standard Output Sensitivity/Recommended Exposure Index.
 According to ISO 12232-2006 (20th April 2006) which specifies the method for assigning and reporting ISO speed ratings for digital still cameras
- 4 Not all functions of the flash are supported
- 5 Recording pixels fixed at 1600 x 1200 6 Large/Fine with LCD monitor off
- 7 Depending on memory card speed/capacity





Service Support

Canon doesn't stop at developing great products, we deliver outstanding after-sales service too. Customers can have complete confidence in their Canon technology with the following benefits;

Helpful, professional Customer Service Advisors

Our team are trained specifically to support Canon products over the phone in order to resolve customers enquiries quickly and efficiently. Customers can call our customer services Helpline on 08705 143723. Lines are open during normal working hours (9am – 5.30pm) and all calls are charged at standard National rates.

Qualified technicians

All technicians receive ongoing product training and are equipped with the tools and resources to provide a first class service.

Original Components

Canon only uses genuine spare parts and components in repairs. This ensures high product performance and protects the product warranty.

Visit www.canon.co.uk for more information.

Canon UK Ltd

Woodhatch Reigate Surrey RH2 8BF 08705 143723 www.canon.co.uk

Canon (Irl) Business Equipment Ltd

Arena Road Sandyford Industrial Estate Dublin 18 Ireland www.canon.ie

Not all products and services are available in all markets. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

All trademarks are acknowledged. All data is based on Canon's standard testing and measuring methods. Errors and omissions excepted.

 ${\it Canon reserves the right to change specifications and physical appearance without notice.}$

All LCD images and print outs shown are simulated for clarity of reproduction.



Canon Inc. www.canon.com

Canon Europa NV www.canon-europe.com

Canon UK Ltd www.canon.co.uk

Canon (Irl) Business Equipment Ltd www.canon.ie

Find the perfect fit with Careers@Canon www.canon-europe.com/about_us/careers/







